



THREAD DIM'S BEFORE PLATING: (G-0695)
 MAJOR DIA. .506 MIN.
 PITCH DIA. .477/.481
 MINOR DIA. .457/.461

THREAD DIM'S AFTER PLATING: (G-0684)
 MAJOR DIA. .505 MIN.
 PITCH DIA. .476/.481
 MINOR DIA. .456/.461

FINISH NOTE:

ELECTRODEPOSITED ZINC COATING WITH SUPPLEMENTARY FINISH PER: ASTM B633-98
 CLASSIFICATION Fe/Zn 12 SERVICE CONDITION SC3 TYPE II YELLOW CHROMATE CONVERSION COATING (SEE NOTE 4)

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M

BILL OF MATERIAL				
CDPLIES TO	MATL SPEC (AS SUPPLIED STEEL POWDER)	FINISH	SEE FINISH NOTE & NOTE 4	
1	9 18 DRW	JMB	DATE 2/18/88	SCALE 2=1
2	10 19	CHK	DATE	SUPER DRW
3	12 20	APPD	DATE	RAW STK WT
4	13 21		DATE	
5	14 23		DATE	
6	15 33		DATE	
7	16 43		DATE	
8	17 53		DATE	
TOLERANCE UNLESS OTHERWISE SPECIFIED TWO PLACE DEC ±.01 FRACTION ±1 THREE PLACE DEC ±.005 ANGULAR ±1°				
LBS/M				
TITLE				
HEX NUT				
HEXAGON DRWG. NO. 903-012				
LITTELFUSE® AT				
DES PLANNES, ILL INOIS 60016				

LTR	REVISION	CHK	APD
AR	39025C- REVISED & REDRAWN ON NEW FORMAT 3/13/98 JMB		
AS	80518C - ADD FINISH NOTE, CHG. NOTE 4		
--	4/4/2000	BJJ	
AT	82142D-CHG F0005-20 TO F-00006-.65 MIN. DEN. 5/22/02 P.J.M		

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
 DENOTES CRITICAL CHARACTERISTICS.
 DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF THE PROCESSING TO BE USED IN THE FABRICATING PROCEDURE FOR MEASUREMENT OF THIS DIMENSION TO THE TOLERANCE SPECIFIED IN THE INSTRUCTIONS.
 DENOTES CP DIMENSIONS - MINIMUM CP VALUE
 DIMENSIONS WITHIN THE DIMENSIONAL LIMITATIONS SHOWN BE WITHIN THE DIMENSIONAL TOLERANCE SPECIFIED FOR MAXIMUM TOOL LIFE.

UNCONTROLLED DOCUMENT

NOTES:

1. AXIS OF THREAD TO BE ⊥ WITHIN 1" TO FACE OF NUT. PITCH DIA. & MAJOR DIA. TO BE CONCENTRIC WITH MINOR DIA. WITHIN .007 T.I.R.
2. PART MUST SPIN FREELY ON "GO" GAGE. PART MAY ENTER "NO-GO" GAGE A MAXIMUM OF TWO THREADS. USE GAGE G-0695 BEFORE PLATING. USE GAGE G-0684 AFTER PLATING.
3. UNPLATED PARTS TO BE PROTECTED AGAINST OXIDATION UNTIL PLATING; PLATING TO BE DONE AS SOON AS POSSIBLE AFTER FABRICATION.
4. PLATED PARTS SHALL MEET THE SALT SPRAY REQUIREMENTS ASTM B-117 96 HOUR SALT SPRAY TEST. (CERTIFICATION REQUIRED).
5. VENDOR & L/F THREAD GAGE CORRELATION REQUIRED.
6. LITTELFUSE TO PLACE 100 NUTS IN BAG -896-259.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fuse Holder Accessories](#) category:

Click to view products by [Littelfuse](#) manufacturer:

Other Similar products are found below :

[BK/1A1337](#) [1A1853](#) [1A4421](#) [1A5220](#) [903-048](#) [1A1337](#) [1A4544](#) [1A5220-01](#) [CO2-10](#) [CO3-03](#) [348897](#) [B072-7007](#) [BK/1A4421](#) [BK/9732](#)
[X30110](#) [09030012H](#) [09050023H](#) [00970021HXNVDL](#) [00BS0232P](#) [CO2-04](#) [BK1A1853](#) [BK9834](#) [0880.0001](#) [00970053XP](#) [3566C](#)
[00970053H](#) [04450718ZX900](#) [CH10CL](#) [BP/FP-3](#) [58600000005](#) [33-012C](#) [880140](#) [00970023S](#) [880150](#) [PDM71009ZXM](#) [B109-7091-4](#) [B109-](#)
[7091-6](#) [B109-7091-5](#) [901-524](#) [CVR-RH-25100](#) [LFH60030FBC](#) [03540514Z](#) [03540526Z](#) [03540531Z](#) [03540541Z](#) [03540525Z](#) [03540537Z](#)
[03540539Z](#) [03540540Z](#) [FEH](#)