

### Fuseholders

#### For Micro™ Fuse or Pico® II Fuses

## "Push-On" Retaining Nut Chassis Mount Type

#### SPECIFICATIONS:

Electrical: Rated at 5 amperes for any voltage up to 125 volts. Mounting: Maximum panel thickness is .09". Molded Parts: Black Thermoset. Terminals: Beryllium Copper, Silver-plated. Ambient Temperature: -40°C to +125°C. Hardware: "Push-On" retaining nut.

\* Please refer to Fuseology section for information on proper fuseholder de-rating.

#### FOR MICRO<sup>™</sup> FUSE OR PICO<sup>®</sup> II FUSES

# Vertical/Horizontal

P.C. Board Mount Type

.**R**.

Vertical

Fuseholder will accept Littelfuse MICRO<sup>™</sup> fuses and PICO<sup>®</sup> II fuses (rated to 5 amperes) with .025" diameter leads. SPECIFICATIONS:

Electrical: Rated at 5 amperes for any voltage up to 125 volts. Molded Parts: White Thermoplastic. Terminals: Copper Alloy.

Ambient Temperature: -40°C to +100°C.

#### ORDERING INFORMATION:

Catalog Number	Terminal Plating	Mounting
<b>281</b> 005	Silver <sup>1</sup>	Vertical
<b>281</b> 008	Tin	Vertical
<b>281</b> 007	Silver	Horizontal
<b>281</b> 010	Tin	Horizontal

<sup>1</sup>UL Recognized.

\* Please refer to Fuseology section for information on proper fuseholder de-rating.




Fuse holder will accept Littelfuse LT-5<sup>™</sup> and TR5<sup>®</sup> fuses up to 5 amperes. **SPECIFICATIONS:** 

Electrical: Rated at 5 amperes for any voltage up to 250 volts. Molded Parts: Black Thermoplastic (UL94 V-O). Terminals: Tin-plated brass, gold inside. ORDERING INFORMATION: Catalog Number: 02800050

\* Please refer to Fuseology section for information on proper fuseholder de-rating.







QPL














13

FUSEHOLDERS

477

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Littelfuse manufacturer:

Other Similar products are found below :

V130LA10A 1SMB33AT3G 1SMA24AT3G 0362030.V 59022-3-S-02-F 46213150000 59022-3-T-02-F 59022-3-U-02-F MDRR-DT-30-35-F SK225RDTP GTCA28-231M-R05 SMBJ5.0 00970019XP LX5090 0217.500HXP 02181.25TXP 0224006.HXUP 740GN 815.650 FLA2.25 FLSR400 FLSR600 900-1535-012RN 901-134 970699013 971-670A-92WCN 153.5631.5601 155100 157.5701.6101 1.5KE110A-B 1.5KE220A 1.5SMC150CA BLF006 BLF008 JLLS-250 235.200 901-152C-042RN 920-401X-330BN 282007 LFC600602CID LFR600303CID LJCA030.X SE-GRM024 SE-TA6ASF-WL 2N6509G 980-788A-070 FLNR100 FLNR400 FLSR200 211RT