

Fuseholders

For Micro™ Fuse Plug-In Fuses

RF-Shielded Front Panel Mount Type / Rear Panel Mount Type

Space Saving. RF-shielded design holds miniature MICRO[™] fuse. Screw-on drip-proof knob construction permits use when presence of moisture exists at front of panels.

SPECIFICATIONS:

Electrical: Rated at 5 amperes for any voltage up to 125 volts.

Mounting: Front panel mount, maximum panel thickness: .093". Rear panel mount, maximum panel thickness: .125".

Molded Parts: Black thermoset.

Housing, Knob and Nut: Aluminum, untreated.

Mounting Gasket: Neoprene or conductive silicone.

Seal: Buna "N" O-ring inside the knob.

Terminals: Beryllium copper. Silver plated.


Ambient Temperature: -40°C to +125°C.


Hardware: Hex nut or knurled nut as shown, unassembled.

* Please refer to Fuseology section for information on proper fuseholder de-rating.













ORDERING INFORMATION:

Catalog Number	Gasket Type
282 001	Neoprene
282 007	Conductive

ORDERING INFORMATION:

Catalog Number	Gasket Type
282 002	Neoprene
282 008	Conductive

13

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Littelfuse manufacturer:

Other Similar products are found below:

V130LA10A ISMB33AT3G ISMA24AT3G 0362030.V 59022-3-S-02-F 46213150000 59022-3-T-02-F 59022-3-U-02-F MDRR-DT-30-35-F SK225RDTP GTCA28-231M-R05 SMBJ5.0 00970019XP LX5090 0217.500HXP 02181.25TXP 0224006.HXUP 740GN 815.650 FLA2.25 FLSR400 FLSR600 900-1535-012RN 901-134 970699013 971-670A-92WCN 153.5631.5601 155100 157.5701.6101 1.5KE110A-B 1.5KE220A 1.5SMC150CA BLF006 BLF008 JLLS-250 235.200 901-152C-042RN 920-401X-330BN 282007 LFC600602CID LFR600303CID LJCA030.X SE-GRM024 SE-TA6ASF-WL 2N6509G 980-788A-070 FLNR100 FLNR400 FLSR200 211RT