

SR SERIES MASTER DISCONNECT SWITCHES

300A • Isolates High-Current DC Circuits From Battery Sources

PN 880064



PN 880062

Description

Stainless steel hardware and tin-plated copper studs. Can be installed in locations with limited space behind the panel.

Specifications Overview

Max Operating Voltage:	48V, 32V DC & 12V DC Single Cycle: 48V DC
Max Continuous Current:	5A-600A
Inrush Rating (2 sec):	3,500A
Terminal Stud Size:	3/8"-16 (accepts M10 terminals)
Ingress Protection:	IP67/IP69K
Ignition Protection:	Meets ISO 8846 & SAE J1171

Web Resources

Download technical resources at:
littelfuse.com/SR


Ordering Information

BULK PART NUMBER	BLISTER PART NUMBER	POLE	MOUNT	MAX VOLTAGE RATING	MAX TOTAL CONTINUOUS CURRENT	TERMINALS
880062	880062-BP	SPST	Flange Mount	48V DC	300A	Two Tin Plated Copper Studs
880064	—	SPST	Panel Mount	48V DC	300A	Two Tin Plated Copper Studs
880154	—	SPST	Panel Mount	32V DC	600A	Two Tin Plated Copper Studs
880064100	—	SPST	Panel Mount	32V DC	300A	Two 3/8 Copper Studs
888842000A	—	SPDT	Panel Mount	12V DC	5A	Molex 33472-0406 MX150
888842001A	—	SPDT	Panel Mount	12V DC	5A	Molex 33472-0406 MX150; Molex 33471-0306 MX150

Features and Benefits

- Isolates the batteries and eliminates battery drain when vehicle is stored overnight or for longer periods. Electrically cuts off battery power for safety or when the vehicle is being serviced.
- Ignition protected to SAE J1171 and ISO 8846 for installation in a battery box or on vehicles carrying hazardous loads.
- Available with integral holes to accept lockout/tagout. No need to purchase additional hardware.
- Plastic construction will not corrode and stands up to roadsplash and salt spray. Ingress protected to IP67/IP69K. Switch can be mounted anywhere on the vehicle.
- Units have a depth of only 3" (knob front to end of studs) – can be installed in locations where behind-panel space is limited.
- Stainless steel hardware and tin-plated copper contacts minimize resistance in harsh environments.

Specifications



Master Battery Disconnect (shown in ON state)

Datasheet Replaces Hotfeed Number D-659

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fuse Holder](#) category:

Click to view products by [Littelfuse](#) manufacturer:

Other Similar products are found below :

[570-290-741P40](#) [570-290-751P40](#) [020417G](#) [020418E](#) [6R30A1B](#) [F600A3B](#) [80910030](#) [8601.2020](#) [G15A2SPQ](#) [9-3557-GP REV A](#) [HDJ-B](#)
[R6J30A3S](#) [HFH-1](#) [RF30A2B](#) [RF30A3SP](#) [15600-08-10](#) [BK/FHN19G](#) [BK/HHM](#) [BK/HKP-CCHH](#) [BK/HKP-JJ](#) [BK/HTJ-LES-FUSE](#) [HMG-](#)
[241](#) [HTJ-LES-FUSE](#) [C4044-1](#) [2086-1](#) [2193](#) [2602](#) [2650](#) [178.000100](#) [FHN31G1](#) [T30A2B](#) [G4PB8](#) [2660](#) [2799](#) [CQ-209V](#) [HKP-CCHH](#)
[R6F30A2S](#) [341001A](#) [345621A](#) [CVRMCC](#) [4202](#) [4407](#) [4408](#) [4413](#) [4423](#) [4532](#) [4537](#) [TSD1404-12](#) [BK/FHN31G1](#) [BK/HC-5](#)