LFPSJ Series POWR-SAFE Class J Fuse Holders

600 V











Description

The Class J POWR-SAFE LFPSJ series dead front fuse holders feature the IP20 touch-safe design for maximum protection to personnel. These fuse holders are available in 1-, 2-, and 3-pole configurations and are offered in indicating and non-indicating options. The LFPSJ series is DIN rail mountable and easily installed and removed with no additional pullers or tools required. These fuse holders are UL 248-8 listed and CSA certified.

Features & Benefits

FEATURES	BENEFITS
IP20 finger-safe design	Maximum safety for personnel
35mm DIN rail mountable	Easy installation in various settings
Compact design	Ultimate flexibility, space-saving
Dual LED indication	Distinguishes polarity in dc power applications
1-, 2-, and 3-pole configurations	Suitable for various applications

Applications

• For use with Class J: JTD, JTD_ID, JLS fuses

LFPSJ Series POWR-SAFE Class J Fuse Holders

Specifications

Voltage Rating Ac: 600 V

Dc: 600 V

Ampere Range 30 and 60 A **Interrupting Ratings** 200 kA

LEDs 110 V - 600 V
Terminal Type Pressure Plate
Material Thermoplastic
Flammability Rating UL94 V-0

Terminal Screws Phillips / Slotted

Applicable Standards UL Listed (File: E14721)

CSA Certified (File: 2529839)

Environmental RoHS Compliant

Country of Origin USA

Certification & Compliance

UL	UL Listed (File: E14721)
CSA	CSA Certified (File: 2529839)
CE	Declaration of Conformity: EU_DOC-LFPSJ_220121
RoHS	RoHS 2 Directive 2011/65/EU; Directive (EU) 2015/863

Accessories

Recommended Class J fuses: JTD, JTD_ID, and JLS

Multi-Pole Assembly Kit

Kits are used to create multi-pole holders from 1-pole LFPSJ fuse holders. Please contact factory for more information.





CONNECTOR PINCER

HANDLE PIN


AMP	POLES	PINCER QUANTITY	PIN QUANTITY	ASSEMBLY SETS	ORDERING NUMBER
30	2	30	10	10	LF3J2PAK
30	3	60	10	10	LF3J3PAK
60	2	30	10	10	LF6J2PAK
60	3	60	10	10	LF6J3PAK

LFPSJ Series POWR-SAFE Class J Fuse Holders

Ordering Information

AMP	POLES	INDICATION	ORDERING NUMBER	РАСК ОТҮ.	WIRETYPE	WIRERANGE	TORQUE
30	1	-	LFPSJ301.Z	6	Stranded	0.75mm² – 1mm² 1.5mm² – 50mm² 18 – 1 AWG	2.5 N-m 4.0 N-m 35 lb-in
	2	-	LFPSJ302.Z	3	Stranded		
	3	-	LFPSJ303.Z	2	Stranded		
	1	•	LFPSJ301.ZXID	6	Stranded		
30	2	•	LFPSJ302.ZXID	3	Stranded		
	3	•	LFPSJ303.ZXID	2	Stranded		
	1	-	LFPSJ601.Z	6	Stranded	2.5mm ² – 50mm ² 14 – 1 AWG	4.0 N-m 35 lb-in
60	2	-	LFPSJ602.Z	3	Stranded		
	3	-	LFPSJ603.Z	2	Stranded		
	1	•	LFPSJ601.ZXID	6	Stranded		
	2	•	LFPSJ602.ZXID	3	Stranded		
	3	•	LFPSJ603.ZXID	2	Stranded		


Dimensions mm (inches)



 ${\it Note: These \ dimensions \ are \ for \ reference \ only. \ Please \ contact \ factory \ for \ additional \ information.}$

LFPSJ Series POWR-SAFE Class J Fuse Holders

Dimensions mm (inches)



Note: These dimensions are for reference only. Please contact factory for additional information.

Disclaimer Notice — Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/product-disclaimer.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Littelfuse manufacturer:

Other Similar products are found below:

0031.1351.01 6R30A1B 6SC30A2IC F30A3S F600A3B 80910030 80910080 9-3557-GP REV A HFH-1 RF30A1S RF30A2B RF30A3SP 15602-04-08-21 HTJ-LES-FUSE RTMF-SC 2602 2650 178.000100 F60A2SQ T30A2B G4PB8 2660 HKP-CCHH R6F30A2S 341001A 345621A 348670 CVRMCC 4202 4408 4423 4532 4537 TSD1404-12 HPC 55900008011 345602-010 345603-010 345612 345903A 3578 3833-5 3833-7 3992 4393 4409 4522 4574 02800031Z ESFH04/HTCC35M