

## **Electric strikes 1761 BI series**

















- Reversible (left and right hand).
- With monitoring.
- ✓ Maximum load of the microswitch AC (125V)-3A/DC (30V)-2A.


**FEATURES** 

- ✓ Height 88 mm., width 20,5 mm.
- For narrow profiles.
- ✓ Fail-safe (NO) models.
- ✓ Assembling screws distance 52 mm.
- ✓ Latch adjustment 4 mm.
- ✓ The power supply is set by jumper settings: 12 or 24 V DC.
- ✓ Low or very low power consumption.
- ✓ Durability: grade C-200 000 cycles.
- ✓ Category of use grade 3 suitable for public buildings.
- ✓ Certyficate of Conformity acc. to EN 14846.



## TECHNICAL DATA





Power supply (V)	12-24V DC
Tolerance (%)	± 5 %
Continuous work	100% 12V DC 100% 24V DC
Resistance (Ω)	45/180
Power consumption (mA)	12V / 260 24V / 130
Max preload DC (N)	10
Working temperature	12V DC = 58 °C 24V DC = 62 °C

Recomended front plates: 900; 901; 902; 903; 913

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Fixings & Accessories category:

Click to view products by Lockpol manufacturer:

Other Similar products are found below:

F03-01 SUS304 BINIL 8000-5130 FH-AP1 PH-1-10M PH-1-20M PH-2-30M AC201 R4 ADI-LC3S E39-L149 EC18-WELL K35-4 A-1923 SS-12143 STA12 PH-1-50M R6 D01051301 43912557-020 MF-1 D=3.2 BGN-035 E39-L7 ZX-SB11 D01070602 606072 606075 Y92ES12PVC4A10ML Y92ES12PVC4S5ML SA9Z-F11 Z49-SF1 E4R-R12A-CS3M010 ZX-SW11E V3 E4R-R12A-CS3M020 BS-1T CHITAN CCS-PD2-1012 PH-2-90M PH-2-5M XMLZL008 AC244 28810-1 PH-1-40M SS-12225 32043-500 ZG2-XC15CR ZS-SW11V3E ZS-MDC11 ZS-DSU11 ZJ-SFW11 Y92E-STS05-05 PH-2 HYPALON 10M