

## **Electric strikes 802 series**
















## **FEATURES**

- ✔ Reversible (left and right hand).
- Unsymmetrical.
- ✓ Height 90 mm., width 20 mm.
- ✓ Fail-secure (NC) and fail-safe (NO) models.
- ✓ Assembling screws distance 52 mm.
- ✓ Latch adjustment 4 mm.
- ✔ Power supply: 12-24 V AC / DC.
- ✓ Low power consumption.
- ✓ Optionally manual release lever, internal automatism (hold open).
- ✓ Durability: grade C 200,000 cycles.
- Category of use grade 3 suitable for public buildings.
- ✓ Certificate of Conformity acc. to EN 14846.

## TECHNICAL DATA



Model	Rel.lever	Hold-Open	NO
812			
822			
834			
844			
811			Ø

Power supply (V)	12-24V AC/DC	12V DC NO	24V DC NO
Tolerance (%)	± 5 %		
Continuous work	< 1 min.	100 %	100 %
Resistance (Ω)	23	60	150
Power consumption DC (mA)	12V / 500 24V / 1000	12V / 200 -	24V / 160 -
Power consumption AC (mA)	12V / 450 24V / 900	-	-
Max preload DC (N)	10	10	10
Max preload AC (N)	90	-	-

Recomended front plates: 900, 901, 902, 903, 913

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Fixings & Accessories category:

Click to view products by Lockpol manufacturer:

Other Similar products are found below:

F03-01 SUS304 BINIL 8000-5130 FH-AP1 PH-1-10M PH-1-20M PH-2-30M AC201 R4 ADI-LC3S E39-L149 EC18-WELL K35-4 A-1923 SS-12143 STA12 PH-1-50M R6 D01051301 43912557-020 MF-1 D=3.2 BGN-035 E39-L7 ZX-SB11 D01070602 606072 606075 Y92ES12PVC4A10ML Y92ES12PVC4S5ML SA9Z-F11 Z49-SF1 E4R-R12A-CS3M010 ZX-SW11E V3 CCS-PL-LDR2-70 E4R-R12A-CS3M020 BS-1T CHITAN F03-01 CHITAN CCS-PD2-1012 PH-2-90M PH-2-5M XMLZL008 AC244 28810-1 PH-1-40M SS-12225 32043-500 ZG2-XC15CR ZS-SW11V3E ZS-MDC11 ZS-DSU11 ZJ-SFW11