

LogiLink_®

HDMI™ Extender Set Over Network Cable

1080p/60 Hz, Extend up to 60 m

Art. No.: HD0023

Allows you to extend HDMI video and audio signals by up to 60 m over a networking cable; with supports resolution up to 1080p/60 Hz. Also, it works to extend IR signals from remote controls of the video source. Perfect for controlling your video source from your video destination.

Features:

- » Supports 1080p@60 Hz up to 60 m over a single Cat. 6/7/8 cable
- » Bandwidth: 2.25 Gbps/225 MHz per channel
- » Supports deep color 8 bit/10 bit per channel (24 bit/30 bit all channels)
- » Compatible with HDCP 1.3
- » Supports Full 3D, DDC (Display Data Channel) and CEC (Consumer Electronics Control)
- » Supports uncompressed audio such as LPCM 7.1
- » Supports compressed audio such as DTS, Dolby Digital (including DTS-HD Master Audio™ and Dolby TrueHD)
- » Features IR return which enables you to control the video source from your video destination
- » Power Over Cable

Transmitter





Receiver



- (a) IR Out: IR signal output port
- (b) HDMI In: connect to HDMI source device
- (c) Connect to DC 5 V Power Supply
- d Reset (equalizer): automatically to adjust the signal to match the cable length
- (e) Ethernet Ports: Connects transmitter (TX) to receiver (RX) via network cable
- (f) Link LED Indicator
- (9) IR In: IR signal input port
- (h) HDMI Out: connect to HDMI display device










Control







Specifications:

| Transmitter (TX) Interface | 1x HDMI-A female, 1x RJ45 | |
|------------------------------------|--|--|
| Receiver (RX) Interface | 1x HDMI-A female, 1x RJ45 | |
| HDMI Version | 1.3 | |
| HDCP Version | 1.3 | |
| Working Distance | 60 m | |
| Output Resolution | 480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz | |
| Video Bandwith | 2,25Gbps/225MHz | |
| CEC (Consumer Electronics Control) | Yes | |
| DDC (Display Data Channel) | Yes | |
| Chassis Material | Metal | |
| 3D Supporting | Yes | |
| LED Indicator | Yes | |
| IR Support | Yes | |
| POC (Power Over Cable) | Yes | |
| Power Consumption | 5 W | |
| Power Supply | 5 V/1 A | |
| Uncompressed Audio | LPCM 7.1 | |
| Compressed Audio | DTS, Dolby Digital, DTS-HD Master Audio™, Dolby TrueHD | |
| Networking Cable | Cat 5e/6/7/8 | |
| Operating Temperature | 0°C-70°C | |
| Operating Humidity | 10%-85% RH (no condensation) | |
| Storage Temperature | -10°C-80°C | |
| Storage Humidity | 5%–90% RH (no condensation) | |
| Dimensions | 8,1x4,8x2,6 cm | |
| Weight | 0,25 kg | |

Specification of External Power Supply:

| Input Voltage | 100–240 V, 50/60 Hz 0,2 A max. |
|---------------|--------------------------------|
| Output Power | 5 V/1 A, 5 W |
| DC Plug | 5,5x2,1 mm |
| Dimensions | 51x35x59 mm |
| Cable Length | 1,2 m |
| Weight | 0,07 kg |



Package Contents:

- » 1x HDMI Extender Set
- » 1x IR TX Cable
- » 1x IR RX Cable
- » 4x Mounting Ears
- » 1x Power Adapters 5 V/1 A
- » 1x User Manual

Package Information:

» Packing Dimension: 190x145x60 mm

» Packing Weight: 0,47 kg

» Carton Dimension: 505x235x340 mm

» Carton Q'ty: 15 pcs

» Carton Weight: 7,5 kg







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Logilink manufacturer:

Other Similar products are found below:

1775247-3 2-1932649-5 30-1231 30-528 2069485-1 30-504 30-519 30-542 47648-2000 2002-400 769-103/021-000 1932649-1 233-368NFG6-17NH PJ-210A PJ-35825 FDB0901-M0DB300K6KF 3VD51203-3D6A-7H DV11201-H5R6-4F DSP-8PH4-03 AK-AD-38 AK-AD-39 A-DPM-HDMIF-002 A-HDMI90-FML A-MDPM-HDMIF4K-01 CDA0109 A-DPM-VGAF-02 CDA0110 CV0045A CCP-DPM-VGAM-6 CC-MDP-HDMI-6 67881 HAFBF HBLBH HBLBI HAFBG HAFBH HAGBF HAGBG HAGBH HAGBI HAGBJ HBLBJ AABIE AABIF AABIG AABIH AABII AABIJ AABIK AABIL