

LogiLink_®

4K 4x1 HDMITM Switch ARC, 4K/60 Hz


Art. No.: HD0046

Allows you easily share a display with four HDMI-enabled A/V devices. Features four independent inputs that each support 4K resolution and 7.1 surround sound audio. Also, the audio embedded in HDMI can be extracted via HDMI, Toslink or Coaxial and the switch can return the audios to AV receivers with audio return channel (ARC) function.

Features:

- » Allows up to four HDMI sources to be connected to one HDMI display
- » Supports manual switching or remote switching
- » Enables the most recently activated video source to be displayed automatically
- » Supports digital audio output simultaneously: Audio-H (HDMI only for audio), Stereo, Toslink and Coaxial
- » Resolution up to UHD 4K@60 Hz (YUV 4:4:4) and Full 3D
- » Bandwidth: 6 Gbps/600 MHz per Channel (18 Gbps total)
- » Supports HDCP 2.2, DDC, HDR, ARC and CEC functions
- » Supports 12bit per channel (36bit all channels) deep color
- » Supports uncompressed audio such as LPCM
- » Supports compressed audio such as DTS, Dolby Digital (including DTS-HD Master Audio™ and Dolby TrueHD)

Front



Back














- (a) Power LED indicator
- (b) HDMI input 1-4 ports LED indicator
- (c) IR signal receiver
- (d) HDMI input switch button
- (e) ARC On/Off button and LED indicator
- (f) 2CH/5.1CH/PASS audio mode switch button and LED indicator
- TV/AMP switch button and LED indicator for PASS mode
- (h) DC 5V input
- (i) HDMI input 1-4 ports
- (j) HDMI output port
- (K) Audio-H: HDMI output audio only
- Audio output ports





Specifications:

4x HDMI-A female, 1x DC Power Jack
1x HDMI-A female, 1x Stereo, 1x Coaxial, 1x Toslink, 1x HDMI Audio
2.0
2.2
Yes
Yes
480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz, 4K@24/25/30 Hz, 4K@50/60 Hz
6 Gbps/600 MHz
Yes
Yes
Yes
Metal
Yes
Yes
5 W max.
5 V/1 A
LPCM 7.1
HDMI: DTS-HD Master Audio™, Dolby TrueHD SPDIF: DTS/Dolby Digital Coaxial: DTS/Dolby Digital
0°C-70°C
10%–85% RH (no condensation)
-10°C-80°C
5%–90% RH (no condensation)
21x6.6x2.6 cm
0.356 kg

Specification of External Power Supply:

Input Voltage	100–240 V, 50/60 Hz 0.2 A max.
Output Power	5 V/1 A, 5 W
DC Plug	5.5x2.1 mm
Dimensions	51x35x59 mm
Cable Length	1.2 m
Weight	0.07 kg



Package Contents:

- » 1x 4K 4x1 HDMI Switch
- » 1x Remote control
- » 1x Power Adapter 5 V/1 A
- » 1x User Manual

Package Information:

» Packing Dimension: 243x196x60 mm» Packing Weight: 0.57 kg

» Carton Dimension: 505x235x340 mm

» Carton Q'ty: 10 pcs » Carton Weight: 6.3 kg





Made in China

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Logilink manufacturer:

Other Similar products are found below:

1775247-3 2-1932649-5 30-1231 30-528 2069485-1 30-504 30-519 30-542 47648-2000 2002-400 769-103/021-000 1932649-1 233-368NFG6-17NH RPI-16338 CCB-HDMIL-1.5M CCB-HDMIL-1M CCB-HDMIL-7.5M CCBP-HDMI-10M CCBP-HDMI8K-2M AK-AV-02 AK-AV-13 AK-AV-15 AK-HD-100A AK-HD-100P AK-HD-15P AK-HD-30P DSP-2PH4-04 DSP-4PH4-02 DSP-8PH4-03 AK-AD-38 AK-AD-39 RPI-14662 RPI-16335 A-DPM-DVIF-002-W A-DPM-DVIF-03-W A-DPM-HDMIF-002 A-DVI-VGA A-HDMI90-FML A-MDPM-DPF-001-W A-MDPM-HDMIF-02-W A-MDPM-HDMIF4K-01 75053 75603 75777 75844 75919 A-DPM-HDMIF-002-W AK-330126-100-S KAB-07040