





Art No. NS0103

5-Port Fast Ethernet Desktop Switch

NS0103 Fast Ethernet Switch, mini and exquisite is specially designed for SOHO and small enterprise users. With easy installation, stable performance and high forwarding rate, it supports Auto MDI/MDIX and auto negotiates the port connection mode.

Features:

- Five 10/100Base-T Fast Ethernet Ports
- Complies with IEEE802.3 10Base-T & IEEE802.3u 100Base-TX Fast Ethernet standards
- Supports IEEE802.3az energy efficient Ethernet function
- Smart Green Ethernet technology to reduce power consumption
- Supports Auto-MDI/MDI-X each port
- Supports Full/Half duplex modes and Auto-Negotiation
- Supports Store-Forward Switching method
- Supports Flow Control, Non-blocking and Jumbo frame performance
- Supports Hardware-based learning, and aging
- Supports 1k MAC address
- Included external power adapter 5V/0.6A (3W)

Specification:

| | 1 |
|------------------------|--------------------------------------|
| Solution | IP175G |
| Protocols/Standards | IEEE 802.3, IEEE 802.3u |
| Interface | 5 x 10/100Mbps RJ45 ports |
| MAC Address Table | 1K |
| Buffer Memory | 56K bytes |
| Switching Fabric | 1Gbps |
| Packet Forwarding Rate | 10M: 14880 pps |
| (in 64 bytes) | 100M: 148800 pps |
| LED Indicator | 1 x Power LED (Power: Green) |
| | 5 x Port LEDs (Link/Activity: Green) |
| Power | External Power supply 5V/0.6A (3W) |
| Power Consumption | Max. AC Input 1.61W |
| | Max DC input 1.07W |











Art No. NS0103

5-Port Fast Ethernet Desktop Switch

| Product Dimension | 99 x 67.6 x 24.5mm |
|-----------------------|------------------------------|
| Case Material | Plastic |
| Operating Temperature | 0°C ~ 40°C |
| Storage Temperature | -20°C ~ 70°C |
| Operating Humidity | 10% ~ 90% RH, non-condensing |
| Storage Humidity | 5% ~ 90% RH, non-condensing |
| Safety | CE, LVD |

Package Contents:

- 1 x 5-Port Fast Ethernet Desktop Switch
- 1 x External Supply 5V/0.6A (3W)
- 1 x User Manual

Packaging Information:

- Packing Dimension: 103 x 82 x 87mm
- Packing Weight: 0.225kg
- Carton Dimension: 465 x 348 x 234mm
- Carton Q'ty: 40pcsCarton Weight: 9.71kg













* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Input Devices category:

Click to view products by Logilink manufacturer:

Other Similar products are found below:

80260-08 M11L0A1 M11L0B1M M21L0H1PX M41C091P100 80260-00 81521-08 FKB4720-103 84250-26 84980-04 84S-AC1-000 C10O0C1P JD-0700EU-2 JM-0800-2 JOY-THUMB JW-T0100 89498-13 89758-05 89886-26 89941-00 FQ-XT G3-A1AM151NNNN G80-3000LSCEU-2 M11C011B TH500P00D4 MJ0FGGRY JM-0800-0 KBCV-4100W MR2110R5BB 60C22-M7-4-020S 67A-DF-3C-060C 84S-BB1-004 81601-26 G8011900LPMUS0 G844420LUBEU0 G84-4700LUCUS-0 89701-26 81485-26 84105-13 V400-W24 5M V400-W23 5M G84-5200LCMEU-2 M11F061P 84Z2029-100 4P182F1D0100 M41L091M M41L091P 60A00-8-050C 84Z2029-78 XD2CF1111