

LogiLink®



USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220

Portable designed for fast charging dual devices simultaneously,
perfect for traveling.



Best Connectivity



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



PA0220



4 052792 057089

Made in China

LogiLink®

USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220



Rapid Charging with PD3.0 and QC3.0

Charge your power-hungry devices with one USB-C PD port and one USB-A fast charging port.



Multiple Protection

Supports overcurrent, overvoltage, overheating and short circuit protections.

Best Connectivity



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



PA0220



4 052792 057089

Made in China

LogiLink®

USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220



Wide Compatibility

Compatible with most mobile devices: smartphones, tablets and much more.



Travel-Ready

Compact size easily fit in to laptop bag or backpack.

Best Connectivity



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



PA0220



4 052792 057089

Made in China

LogiLink®



USB-C™ 2-Port Wall Charger, 18W

1 x USB-C™ PD Port & 1 x QC USB Port

Art. No.: PA0220

Specification:

Input	100 - 240V AC 50/60Hz 1A max.
Output	USB-A port: 5V 3A (15W) / 9V 2A (18W) / 12V 1.5A (18W) USB-C port: 5V 3A (15W) / 9V 2A (18W) / 12V 1.5A (18W) *Max. Total Output 18W
Protections	Overcurrent, overvoltage, overheating and short circuit
Efficiency	Level V
Operating Temperature Range	0~40°C
Storage Temperature Range	-40°C ~ 85°C
Relative Humidity	25% ~ 90% (non-condensing)
Storage Humidity	10%~90% (non-condensing)
Dimension	89 x 51 x 29mm
Weight	62g



Package Contents:

- » 1 x USB Wall Charger
- » 1 x User Manual

Package Information:

- » Packing Dimension: 138 x 75 x 45mm
- » Packing Weight: 0.107kg
- » Carton Dimension: 465 x 315 x 167mm
- » Carton Q'ty: 40pcs
- » Carton Weight: 4.98kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



PA0220

4 052792 057089

Made in China

Best Connectivity

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Logilink manufacturer](#):

Other Similar products are found below :

[AA0031](#) [AA0035](#) [AA0039B](#) [AA0039W](#) [AA0050](#) [AA0063](#) [AA0065](#) [AA0069](#) [AA0089](#) [AA0103](#) [AA0104](#) [AA0105](#) [AA0107](#) [AA0112](#)
[AA0113](#) [AA0115](#) [AA0119](#) [AA0120](#) [AA0121](#) [AA0122](#) [AA0153](#) [AD0001](#) [AD0002](#) [AD0008](#) [AD0009](#) [AD0010](#) [AD0011](#) [AD0013](#) [AD0014](#)
[AD0015](#) [AD0017](#) [AD0019](#) [AD0020](#) [AD0021](#) [AD0022](#) [AH0001](#) [AH0002](#) [AH0005](#) [AH0006](#) [AH0007](#) [AH0008](#) [AH0009](#) [AH0010](#) [AH0011](#)
[AH0012](#) [AH0014](#) [AH0015](#) [AU0002E](#) [AU0003C](#) [AU0004A](#)