

LOCK SWITCH



WRL IP66/IP67 SEALED LOCK SWITCH

ELECTRICAL & MECHANICAL SPECIFICATION

Switch Rating: 1A @24V ac/dc Life: >10,000 Cycles

Proof Voltage: 750 Vac (Initial) Lock Type: 5 Disc

Insulation Resistance: >999M Ω @ 500Vdc (Initial) Operating Temperature: -20°C to +65°C

Contact Resistance: $<20m\Omega$ (Initial) Lock Housing: Zinc Alloy Bright Cr Plated

Contact Material: Brass CZ108, Ag Plated **Moulding Material**: Polyamide 6.6 G.F. VO Rated

FEATURES


Suitable for Marine Environment Exposure to Severity One (EN60068-2-52) salt mist tested

Front assembly
Single or Double pole
Max panel thickness 3.5mm
Rear panel depth - <30mm
Made in UK

2 keys per switch Up to 200 differ key combinations available Keys are double entry (can be inserted into lock either way up) Moulded bezel available for parallel lock headed version (SRL02101). Oil regularly if used outside



SINGLE POLE LOCK SWITCH




Positions
For centre off, link pins 1 & 3, Types T and Q only



TAPERED LOCK HEAD 90° INDEXING

BASIC PART No.	TOTAL MOVEMENT	INDEXING	KEY WITHDRAWAL POSITIONS	SWITCH CONFIGURATION
WRL-5-D	90°	90°	1,4	12
WRL-5-E	90°	90°	1 ONLY	
WRL-5-F WRL-5-V WRL-5-W	180° 180° 180°	90° 90° 90°	1,4,7 1,4 1 ONLY	1 OFF 2 3
WRL-5-P	180°	90°	1,4,7	1
WRL-5-T	180°	90°	1,4,7	1 OFF
WRL-5-Q	180°	90°	4 ONLY	3 — OFF

DOUBLE POLE LOCK SWITCH



TAPERED LOCK HEAD 60° INDEXING

BASIC PART No.	TOTAL MOVEMENT	INDEXING	KEY WITHDRAWAL POSITIONS	SWITCH CONFIGURATION
WRL-3-L	60°	6D°	1,3	
WRL-5-M	60°	6D°	1 ONLY	=:

WRL ORDERING CODE



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Keylock Switches category:

Click to view products by Lorlin manufacturer:

Other Similar products are found below:

89496-09 58J1007 58J8A45-01B05N 719-0201-000 719-0202-000 719-0702-000 719-5504-000 84800-04 GKNC33L GKNC3L

PVA2OAH5 HA1K-2C2VA-2 14-136.025K 14-235.022K AS6H-2K2A AS6M-2K1B AS6Q-2K2A AS6Q-3K2A 1571487-1 HW4K-2BF20

KEY-AS6 KH3C-20C 8928K493 2SWK131AL102 AS6M-2K1A AS6Q-2K1PB 51-401.036D 51-401.036K 51-414.036D HW1K-31BF20

HW1K-3HF20 Y1112-2027CLFT 51-155.025D 51-295.022D 51-404.036D 51-405.036D 51-415.036D 1-1437597-8 58J8A36-01B04N

58M1422 86945-05 719-0204-000 719-0205-000 719-0801-000 719-0804-000 719-0805-000 88422-18 58J8A90-01C02N 58J9P36
01B09N 58J8A36-01C03N