

# Product Overview

## SMA Connector Gold Plated SMA Coaxial Connector



A straight SMA female RF coaxial connector for SMA male RF antennas.

Impedance: 50Ω.

Connector mounting: PCB mount.

Working voltage – 335V Max

Insulation resistance -  $\geq 5000\text{m}\Omega$

Dielectric withstand voltage- 1000V rms







Frequency range – DC-12.4GHz

Insertion loss  $\geq 1.05$  dB/6 GHz

Temperature range -  $-65^{\circ}\text{C}$  to  $165^{\circ}\text{C}$



Dimensions in mm:



Product Code: SMACONNECTOR

Order code: SMACONNECTOR



**Low Power Radio Solutions Ltd**  
Two Rivers industrial Estate  
Station Lane, Witney OX28 4BH, UK  
+44(0) 1993 709418  
sales@lprs.co.uk

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:*

*Click to view products by [LPRS](#) manufacturer:*

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [980-8666-005](#) [1200690078](#) [1-201144-1](#) [R107003010W](#)