a lumbergautomation

A BELDEN BRAND



0906 UTP 302 | 0906 UTP 302-Y




DeviceNet T-Connectors / Taps

M12 Female to 1 x 7/8" Male and 1 x 7/8" Female

Splitter/T-connector, with one M12 female, one 7/8" male and one 7/8" female connectors, 5-poles.


– especially suitable for DeviceNet and
CANopen modules with M12 bus connection –

0906 UTP 302 I 0906 UTP 302-Y






Pin Assignments



Willing Diagrafii	
1>-	_

14/:--:--





DeviceNet T-Connectors / Taps

0906 UTP 302 | 0906 UTP 302-Y

Technical Data

Environmental

Degree of protection	IP 68 / NEMA 6P
Operating temperature range	-40°C (-40°F) / +90°C (+194°F)

Mechanical

Housing / Molded body	PUR, yellow
Insert	PUR
Contact	CuZn, pre-nickeled and
	gold-plated acc. to DeviceNet specification
Coupling nut	Aluminum, e-coated or anodized black (7/8")

Electrical

Nominal current

Nominal voltage

Brass, nickel plated (M12)

Trunk:	8 A
Drop:	4 A
60 V	

Part Number	Pins	Characteristics
0906 UTP 302	5	
0906 UTP 302-Y	5	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below :

600X518037XMA1EAF12006STD15PCR99B70A8R4000A16M0208R4A00A18M0208R5000A16M005120091000812009100111300140094130203-00541300150099RF-12S1N8A90DU1-3637-600-520516126188R4006A16M0108R5006A18A12016042321R3006A20M005RF-12P1N8A80DURF-12P1N8A90DU41-0101641-4001141-4001742-010154-22279-44-22281-14-22284-943-0000243-0116641-4000541-4001643-0016143-01191XS3P-M421-2600X518050XSACC-DSI-FS-5P-PG9-L180 SC8R4006A16A1208R4000A16M010RKC 50/161R3004A20A12016-22279-3N03FA031441300140077XS8A-0441859RD04-103R004860RD04-113R004860RD04-213R004860-X08-213R0041-213245-22273142-22273142-2444