




## 0931 DNC 301



## **Passive DeviceNet Distribution Box**

## 8 x M12

Passive DeviceNet distribution box, 7/8" Bus-In/Bus-Out connection for Trunk line, 8 x M12 branches for Drop line.



## **Pin Assignment**

Bus connection 7/8"



1 = Drain 2 = 24 V <sup>1</sup> 3 = GND (0 V) <sup>1</sup> 4 = CAN\_H 5 = CAN\_L





1 = Drain 2 = + 24 V 3 = GND (0 V) 4 = CAN\_H 5 = CAN\_L

# **DeviceNet**

# Be Certain with Belden

# **Passive DeviceNet Distribution Box**

0931 DNC 301

#### **Technical Data**

**Environmental** 

Degree of protection IP 67

Operating temperature range -10°C (+14°F) to +60°C (+140°F)

Mechanical

Weight 350 g Housing material PUR

Total current max. 8 A / max. 3 A per M12 branch

**Part Number** 

0931 DNC 301

The application of these products in harsh environments should always be checked before use. Specifications subject to alteration.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 RSC 4/9 XS2R-D426-1 XS8A-0441 859RD04-103R004