

Industrial Ethernet Panel-Mount Adaptors for PROFINET or EtherNet/IP Applications









Туре	0981 ENC 100	
Product description	RJ45/M12 adaptor, female receptacle connector M12, D coding, chassis side thread PG 9, RJ45 female connector, 90 degree.	
Environmental		
Degree of protection	IP 20 / IP 67	
Operating temperature range	0°C (32°F) to +70°C (+158°F)	
Materials		
Housing	PA	
M12		
Contacts	CuZn, pre-nickeled and gold-plated	
Housing	CuZn, nickel-plated	
insert	PUR, self extinguishing	
0-ring	FKM	
RJ45		
Contacts	CuSn, pre-nickeled and gold-plated	
Housing	CuZn, tin-plated	
Insert	PA GF	
Electrical		
Nominal current	1.5 A	
Nominal voltage	max. 60 V	

The application of these products in harsh environments should always be checked before use. Specifications subject to alteration.

Pin assignment M12 Socket RJ45 Jacket 1 = TD+ 5 = n.c. 2 = TD- 6 = RD3 = TD- 2 = RD4 = RD5 = shield 1 = TD+ 5 = n.c. 2 = TD- 6 = RD3 = RD+ 7 = n.c. 4 = n.c. 8 = n.c.

Part number	Order number	
0981 ENC 100	63484	((++++)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHJ-4P4C-1-V-4 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 E5288-S000K3-L E5908-15A242-L 155302-001