M12-Splitters/T-Connectors


ASBS 2 M8 | ASBS 2 M12 | ASBSA 2 M12



M12 Male to 2xM8 Female

Splitter/T-connector, with two M8 miniature female connectors, 3 poles, with self-locking threaded joint.

ASBS 2 M8



M12 Male to 2xM12 Female

Splitter/T-connector with two M12 female connectors, with self-locking threaded joint.


- ASBS 2 M12-5 1-1: wired through 1 to 1 -

M12 Male to 2xM12 Female

Splitter/T-connector with two M12 female connectors, with self-locking threaded joint.


- ASBSA 2 M12-3: with AND circuit -

ASBS 2 M12




- *a coupling nut black
- *b coupling nut nickel-plated

ASBSA 2 M12



Pin Assignments

Face Views		
ASBS 2 M8	Α	В
3	3 0 0 1	3 0 0 1
ASBSA 2 M12-3	Α	В
3 0 0 2 n.c.	3 0 0 1	3 0 0 1
ASBS 2 M12-4	Α	В
4 3	300	300
ASBS 2 M12-5S	Α	В
1 2	3 4 0 0 1	n.c. 5
ASBS 2 M12-5	Α	В
4 3	3 0 0 4 0 0 1	3 0 0 4



Be Certain with Belden



M12-Splitters/T-Connectors

ASBS 2 M8 | ASBS 2 M12 | ASBSA 2 M12

Technical Data

Environmental

Degree of protection IP 67 / NEMA 6P

Operating temperature range -25°C (-13°F) / +90°C (+194°F)

Mechanical

Housing / Molded body TPU, self-extinguishing Insert Female connectors:

M8: TPU, self-extinguishing M12: PA GF, self-extinguishing

Male connector:

TPU, self-extinguishing Contact CuZn, pre-nickeled and

0.8 microns gold-plated

Coupling nut CuZn, nickel-plated

O-ring FKM

Electrical

Contact resistance $\leq 5 \text{ m}\Omega$

Nominal current at 40°C 4 A per outlet / 4 A max. total

Nominal voltage 60 V Rated voltage 63 V

Test voltage M8: 0.8 kV eff. / 60 s M12: 1.5 kV eff. / 60 s

ASBSA: 2.0 kV eff. / 60 s

Insulation resistance $> 10^9 \, \Omega$

Pollution degree 3

Part Number		Pins	Characteristics
ASBS 2 M8		3	
	ASBSA 2 M12-3		
	ASBS 2 M12-4	4	
	ASBS 2 M12-5S	5	
	ASBS 2 M12-5		
	ASBS 2 M12-5 1-1		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004