

M12-Receptacle Connectors In Accordance With IEC 61076-2-101

FWD 5 I FWD 5B





Male, 5-Pole


Receptacle connector, combined FIXCON/M12 male connector to combined FIXCON/M12 female connector.

especially designed for use as panel feed through –

FWD 5 I FWD 5B







Pin Assignments

Face Views / M12

Male Connector : 5 poles



Female Connector: 5 poles



Male Connector: 5 poles B Coding



Female Connector: 5 poles B Coding



Be Certain with Belden



M12-Receptacle Connectors In Accordance With IEC 61076-2-101

FWD 5 | FWD 5B

Technical Data

Environmental

Degree of protection IP 67 / NEMA 6P

Operating temperature range -25°C (-13°F) / +80°C (+176°F)

Mechanical

Housing / Molded body CuZn, nickel-plated

Insert Male connector PA 6.6

Insert Female connector TPU, self-extinguishing Contact CuZn, pre-nickeled and 0.8 microns gold-plated

0-ring FKM

Electrical

Contact resistance \leq 5 m Ω Nominal current at 40°C 4 A 60 V Nominal voltage

1.5 kV eff. / 60 s Test voltage Insulation resistance $> 10^9\,\Omega$

Pollution degree

Part Number	Pins	Characteristics
FWD 5	5	
FWD 5B	5B	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004