
Range of application

Connector	351..., 351...-2, 351...-4, 3520, 3521, 3522, 3523, 352...-2
Pole number	2-10 (with pitch 2.5 mm)
Pitch	2,5/5,0 mm
State of delivery of connectors	in chain, to be detached before use of the manual tongs
Processable conductor	discrete conductor, notched flat cable 2.5/5.0 mm

Features

Application	laboratory and sample production, harness repair
Stroke capacity	ca. 240/h
Scope of functions and delivery	- Harnessing of bus cables possible - In transport case - The handle color may vary during a period of transition.
Options	- Special press die, required for 351... with side P1 being closed

Dimensions and supply data

Dimensions (H x W x D)	50 mm x 60 mm x 240 mm
Weight	ca. 1 kg

97

HZ35

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
HZ35	-		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Crimpers / Crimping Tools](#) category:

Click to view products by [Lumberg](#) manufacturer:

Other Similar products are found below :

[010-0096](#) [M225201-06](#) [M225202-37](#) [6-1579015-5](#) [CT150-2-D02](#) [CT150-6-RH07](#) [622-6441LF](#) [M322](#) [6-304052-1](#) [63456-0054](#) [63484-3701](#)
[63800-8355](#) [63819-1875](#) [63819-2875](#) [63819-4475](#) [63823-3475](#) [63827-5375](#) [64001-0975](#) [64001-4175](#) [64005-0175](#) [662903-2](#) [690602-6](#) [7-](#)
[1579001-9](#) [7-23471-1](#) [762637-1](#) [808714-1](#) [811242-5](#) [91362-1](#) [999-50-020083](#) [1-21002-3](#) [1-21002-7](#) [12085270](#) [1-21002-6](#) [1-21113-6](#) [1-](#)
[22548-4](#) [125442-1](#) [DCE.91.073.BVC](#) [DCE.91.090.3MVM](#) [DCE.91.130.5MVU](#) [DCE.91.202.BVCM](#) [1338300-1](#) [1-354003-0](#) [1338301-1](#)
[DF62/RE-MD](#) [142321](#) [AP105-DF11-2428S\(64\)](#) [1456088-1](#) [1490794-1](#) [1-45804-6](#) [1490357-2](#)