


#### **M12 Field Attachable Connectors**

#### RSC | RKC




#### Male, 3-, 4-, 5-, and 8-Pole

Field attachable connector, M12 male connector, 3-, 4-, 5-, and 8-pole with threaded joint, assembling with screw terminals.




#### **RSC**






#### Female, 3-, 4-, 5-, and 8-Pole

Field attachable connector, M12 female connector, 3-, 4-, 5-, and 8-pole with threaded joint, assembling with screw terminals.



#### RKC





#### **Pin Assignments**

Face Views / M12, Male / Female

3 pole





















# eld Attachable Connectors

Field Attachable Connectors

### Be Certain with Belden

#### **M12 Field Attachable Connectors**

RSC | RKC

#### **Technical Data**

**Environmental** 

Degree of protection IP 67 / NEMA 6P

Operating temperature range  $-25^{\circ}\text{C} (-13^{\circ}\text{F}) / +90^{\circ}\text{C} (+194^{\circ}\text{F})$ 

Mechanical

Housing / Molded body PBT Insert PBT

Contact CuZn, pre-coppered, CuSnZn

8-poles pre-nickeled, gold-plated

Receptacle shell CuZn, nickel-plated

O-ring FKM

Mode of connection Screw terminals

Connectable conductor 3–5 poles max. 0.75 mm<sup>2</sup>

8 poles max. 0.50 mm<sup>2</sup>

**Electrical** 

 $\begin{array}{ll} \mbox{Contact resistance} & \leq 5 \mbox{ m} \Omega \\ \mbox{Nominal current at } 40\mbox{°C} & 3-5 \mbox{ poles } 4 \mbox{ A} \\ \end{array}$ 

8 poles 2 A

Nominal voltage 3–4 poles 240 V

5 poles 60 V

8 poles 30 V

Rated voltage 3–4 poles 250 V 5 poles 63 V

8 poles 36 V

Test voltage 3–4 poles 2.0 kV eff. / 60 s

5 poles 1.5 kV eff. / 60 s  $\,$ 

8 poles 0.9 kV eff. / 60 s

Insulation resistance  $> 10^9 \Omega$ 

Pollution degree 3

Part Number		Pins	Cable Diameter Range	Characteristics
Male	Female			
RSC 3/7	RKC 4/3/7	3	Ø 3.0-6.5 mm /SW 15	<b>A</b>
RSC 3/9	RKC 4/3/9		Ø 4.0-8.0 mm /SW 19	<b>A</b>
RSC 4/7	RKC 4/7	4	Ø 3.0-6.5 mm /SW 15	
RSC 4/9	RKC 4/9		Ø 4.0-8.0 mm /SW 19	
RSC 5/7	RKC 5/7	5	Ø 3.0-6.5 mm /SW 15	<b>A</b>
RSC 5/9	RKC 5/9		Ø 4.0-8.0 mm /SW 19	<b>A</b>
RSC 8/9	RKC 8/9	8	Ø 4.0-8.0 mm /SW 19	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X MA1EAF1200 6STD15PCR99B70A 8R4000A16M020 8R4A00A18M020 8R5000A16M005 1200910008 1200910011 1300140094 130203-0054 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-01016 41-40011 41-40017 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00002 43-01166 41-40005 41-40016 43-00161 43-01191 XS3P-M421-2 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R4006A16A120 8R4000A16M010 RKC 50/16 1R3004A20A1201 6-22279-3 N03FA03144 1300140077 XS8A-0441 859RD04-103R004 860RD04-113R004 860RD04-213R004 860-X08-213R004 1-213245-2 2273142-2