


M12 Field Attachable Connectors

RKC/LED | RKCW/LED




Female, 4-Pole (LED)

Field attachable connector, M12 female connector, 4-pole with threaded joint and LED operation and function indicator, assembling with screw terminals (printed circuit board included).



RKC/LED









Female, 4-Pole (90°, LED)

Field attachable connector, M12 female connector, 4-pole with threaded joint and LED operation and function indicator, assembling with screw terminals (printed circuit board included).



RKCW/LED



Pin Assignments

Face Views / M12, Male / Female

4 pole





Connectors

Be Certain with Belden



M12 Field Attachable Connectors

RKC/LED | RKCW/LED

Technical Data

Environmental

Degree of protection IP 67 / NEMA 6P

Operating temperature range -25°C (-13°F) / +90°C (+194°F)

Mechanical

Housing / Molded body PBT Insert PBT

Contact CuZn, pre-coppered, CuSnZn

Receptacle shell CuZn, nickel-plated

O-ring FKM

Mode of connection Screw terminals
Connectable conductor max. 0.75 mm²

Electrical

 $\begin{array}{lll} \mbox{Contact resistance} & \leq 5 \ \mbox{m}\Omega \\ \mbox{Nominal current at } 40 \mbox{°C} & 4 \ \mbox{A} \\ \mbox{Nominal voltage} & 10 - 30 \ \mbox{V} \\ \mbox{Rated voltage} & 32 \ \mbox{V} \\ \mbox{Insulation resistance} & > 10^9 \ \Omega \\ \mbox{Pollution degree} & 3 \end{array}$

Part Number		Pins	Cable Diameter Range	Characteristics
Female	Female 90 $^{\circ}$			
RKC/LED 4/7	RKCW/LED 4/7	4	Ø 3.0-6.5 mm /SW 15	
RKC/LED 4/9	RKCW/LED 4/9		Ø 4.0-8.0 mm /SW 19	<u> </u>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X MA1EAF1200 6STD15PCR99B70A 8R4000A16M020 8R4A00A18M020 8R5000A16M005 1200910008 1200910011 1300140094 130203-0054 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-01016 41-40011 41-40017 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00002 43-01166 41-40005 41-40016 43-00161 43-01191 XS3P-M421-2 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R4006A16A120 8R4000A16M010 RKC 50/16 1R3004A20A1201 6-22279-3 N03FA03144 1300140077 XS8A-0441 859RD04-103R004 860RD04-213R004 860RD04-213R004 860-X08-213R004 1-213245-2 2273142-2