

M8 Field Attachable Connectors

Field attachable connector, M8 male connector


3- and 4-pole with threaded joint, assembling

Male, 3- and 4-Pole

with solder connections.

RSMC

RKMC









Female, 3- and 4-Pole

Field attachable connector, M8 Female connector 3- and 4-pole with threaded joint, assembling with solder connections.



*a O-Ring *b Screw joint for cab**l**e

Pin Assignments

Face Views / M12, Male / Female				
3 pole	4 pole			



RSMC | RKMC

Be Certain with Belden

M8 Field Attachable Connectors RSMC | RKMC

Technical Data

Environmental

Entri onnontar	
Degree of protection	IP 67 / NEMA 6P
Operating temperature range	RSMC: -25°C (-13°F) / +80°C (+176°F)
	RKMC: -40°C (-40°F) / +85°C (+185°F)
Mechanical	
Housing / Molded body	RSMC: CuZn, nickel-plated
	RKMC: PBT
Insert	PA
Contact	RSMC: CuZn, pre-nickeled and
	0.8 microns gold-plated
	RKMC: CuSn, gold-plated

CuZn, nickel-plated

RSMC: max. 0.34mm² RKMC: max. 0.25 mm²

FKM (only RKMC) Solder connection

Receptacle shell O-ring Mode of connection Connectable conductor

Electrical

Contact resistance	$\leq 5 \text{ m}\Omega$
Nominal current at 40°C	4 A
Nominal voltage	3 poles 60 V
	4 poles 30 V
Rated voltage	3 poles 63 V
	4 poles 36 V
Test voltage	RSMC:
	3 poles 1.5 kV eff. / 60 s
	4 poles 0.8 kV eff. / 60 s
Insulation resistance	> 10 ⁹ Ω
Pollution degree	3

Part Number		Pins	Cable Diameter Range	Characteristics	Field Att Conno
Male	Female				ttacha
RSMC 3	RKMC 3	3	Ø 3.5-5.0 mm		able rs
RSMC 4	RKMC 4	4	Ø 3.5-5.0 mm		



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-005413001400261300150099RF-12S1N8A90DU1-3637-600-52051612618210368364148R4006A16M0108R5006A18A12016042321R3006A20M005RF-12P1N8A80DURF-12P1N8A90DU41-4001142-010154-22279-44-22281-14-22284-943-0011343-0108843-0120341-4001342-0000843-0034343-0103243-0116243-10000600X518050XSACC-DSI-FS-5P-PG9-L180 SC8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-01338XS2RD4265RSC 4/9XS2R-D426-1XS8A-0441