

M8 Field Attachable Connectors


RSMCK I RKMCK



Male, 3- and 4-Pole

Field attachable connector, M8 male connector, 3- and 4-pole with threaded joint, assembling with screw terminals.

RSMCK








Female, 3- and 4-Pole

Field attachable connector, M8 female connector 3- and 4-pole with threaded joint, assembling with screw terminals.

RKMCK





Pin Assignments

Face Views / M12, Male / Female

3 pole

4 pole









ield Attachable Connectors

Be Certain with Belden



M8 Field Attachable Connectors

RSMCK | RKMCK

Technical Data

Environmental

Degree of protection IP 67 / NEMA 6P

Operating temperature range $-40^{\circ}\text{C} (-40^{\circ}\text{F}) / +85^{\circ}\text{C} (+185^{\circ}\text{F})$

Mechanical

Housing / Molded body PA

Insert TPU, self-extinguishing
Contact CuZn, pre-nickeled and
0.8 microns gold-plated
Receptacle shell CuZn, nickel-plated

O-ring FKM

Mode of connection Screw terminals
Connectable conductor 0.14-0.50 mm²

Electrical

 $\begin{array}{ll} \mbox{Contact resistance} & \leq 5 \mbox{ m} \Omega \\ \mbox{Nominal current at 40°C} & 4 \mbox{ A} \end{array}$

Nominal voltage 3 poles 60 V 4 poles 30 V

Rated voltage 3 poles 63 V 4 poles 36 V

Test voltage 3 poles 1.5 kV eff. / 60 s

4 poles 0.8 kV eff. / 60 s

 $\begin{array}{ll} \mbox{Insulation resistance} & > 10^9 \, \Omega \\ \mbox{Pollution degree} & 3 \end{array}$

Part Number		Pins	Cable Diameter Range	Characteristics
Male	Female			
RSMCK 3	RKMCK 3	3	Ø 3.5-5.0 mm	
RSMCK 4	RKMCK 4	4	Ø 3.5-5.0 mm	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004