

M12 Field Attachable Connectors (DUO)


RSC...DUO | RKC...DUO



Male, 4- and 5-Pole

Field attachable connector, M12 Duo male connector, 4- and 5-pole with threaded joint, for two cable connections, assembling with screw terminals.

RSC...DUO








Female, 4- and 5-Pole

Field attachable connector, M12 Duo female connector, 4- and 5-pole with threaded joint, for two cable connections, assembling with screw terminals.

RKC...DUO





*a O-Ring

Pin Assignments

Face Views / M12, Male / Female

4 pole





5 pole





ield Attachable Connectors

Be Certain with Belden



M12 Field Attachable Connectors (DUO)

RSC...DUO | RKC...DUO

Technical Data

Environmental

Degree of protection IP 67 / NEMA 6P

Operating temperature range -25°C (-13°F) / +90°C (+194°F)

Mechanical

Housing / Molded body PBT Insert PBT

Contact CuZn, pre-coppered, CuSnZn

Receptacle shell CuZn, nickel plated

O-ring FKM

Mode of connection Screw terminals
Connectable conductor max. 0.75 mm²

Electrical

 $\begin{array}{ll} \mbox{Contact resistance} & \leq 5 \mbox{ m} \Omega \\ \mbox{Nominal current at } 40\mbox{°C} & 4 \mbox{ A} \\ \end{array}$

Nominal voltage 4 poles 240 V

5 poles 60 V

Rated voltage 4 poles 250 V

5 poles 63 V

Test voltage 4 poles 2.0 kV eff. / 60 s

5 poles 1.5 kV eff. / 60 s

Insulation resistance $$>10^{9}\,\Omega$$

Pollution degree 3

Part Number		Pins	Cable Diameter Range	Characteristics
Male	Female			
RSC 4/DUO	RKC 4/DU0	4	2 x 3 mm / 2 x 5 mm	
RSC 5/DU0	RKC 5/DUO	5	2 x 3 mm / 2 x 5 mm	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004