

## M23 Field Attachable Connectors


RSC-F-120/13.5 | RSC 190/9



### Male, 12-Pole

Field attachable connector, M23 male connector 12-pole with threaded joint, external thread, assembling with solder connections.


RSC-F-120/13.5



### Male, 19-Pole

Field attachable connector, M23 male connector, 19-pole with threaded joint, assembling with solder connections.

RSC 190/9



## Pin Assignments

M23 - Male

12 poles



19 poles





# Be Certain with Belden

## M23 Field Attachable Connectors

RSC-F-120/13.5 | RSC 190/9

### Technical Data

#### Environmental





Degree of protection	RSC-F-120/13.5: IP 67 RSC 190/9: IP 65
Operating temperature range	RSC-F-120/13.5: -40°C (-40°F) / +90°C (+194°F) RSC 190/9: -25°C (-13°F) / +110°C (+230°F)

#### Mechanical

Housing / Molded body	CuZn, nickel-plated
Insert	RSC-F-120/13,5: PBT GF RSC 190/9: PA
Contact	CuZn, pre-nickel and gold-plated
Receptacle shell	CuZn, nickel-plated
O-ring	FKM (only RSC-F-120/13,5)
Mode of connection	solder connection
Connectable conductor	max. 1.0 mm <sup>2</sup>

#### Electrical

Contact resistance	RSC-F-120/13,5: ≤ 5 mΩ RSC 190/9: ≤ 3 mΩ
Nominal current at 40°C	RSC-F-120/13,5: 8 A RSC 190/9: 16 x 8 A / 3 x 10 A
Nominal voltage	150 V
Test voltage	1.5 kV eff. / 60 s
Insulation resistance	> 10 <sup>9</sup> Ω
Pollution degree	3

Part Number	Pins	Cable Diameter Range	Characteristics
<b>Male</b>	<b>Male</b>		
RSC-F-120/13.5	12	Ø 10.0 - 14.0 mm	 
	RSC 190/9	19	Ø 6.0 - 10.0 mm
			 

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular Metric Connectors](#) category:*

*Click to view products by [Lumberg](#) manufacturer:*

Other Similar products are found below :

[600X518037X](#) [MA1EAF1200](#) [6STD15PCR99B70A](#) [8R4000A16M020](#) [8R4A00A18M020](#) [8R5000A16M005](#) [1200910008](#) [1200910011](#)  
[1300140094](#) [130203-0054](#) [1300150099](#) [RF-12S1N8A90DU](#) [1-3637-600-5205](#) [1612618](#) [8R4006A16M010](#) [8R5006A18A120](#) [1604232](#)  
[1R3006A20M005](#) [RF-12P1N8A80DU](#) [RF-12P1N8A90DU](#) [41-01016](#) [41-40011](#) [41-40017](#) [42-01015](#) [4-22279-4](#) [4-22281-1](#) [4-22284-9](#) [43-](#)  
[00002](#) [43-01166](#) [41-40005](#) [41-40016](#) [43-00161](#) [43-01191](#) [XS3P-M421-2](#) [600X518050X](#) [SACC-DSI-FS-5P-PG9-L180 SC](#) [8R4006A16A120](#)  
[8R4000A16M010](#) [RKC 50/16](#) [1R3004A20A1201](#) [6-22279-3](#) [N03FA03144](#) [1300140077](#) [XS8A-0441](#) [859RD04-103R004](#) [860RD04-113R004](#)  
[860RD04-213R004](#) [860-X08-213R004](#) [1-213245-2](#) [2273142-2](#)