

## Product information

### M12 Receptacle connector, for sensors - RSE 5

Industrial Connecting Solutions: Circular Connectors: M8 - M12 Connectors: M12 Connectors: M12 Circular connector acc. to IEC 61076-2-101: M12 Receptacle Connectors: M12 Receptacle connector, for sensors

<https://e-catalog.hirschmann.com:443/link/57078-24228-256281-256292-256304-58429-58480-76128/en/RSG-05-k-v-x-z/uistate>

<b>Name</b>	M12 Receptacle connector, for sensors
	
	Receptacle connector, M12 male connector for sensors, press-in tube mounting, with short solder contacts, without antirotation protection, 5 poles, A coding, Pin 5 leading (Standard), without ventilation hole.
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Type</b>	RSE 5
<b>Order No.</b>	11613
<b>Description</b>	Receptacle connector, M12 male connector for sensors, press-in tube mounting, with short solder contacts, without antirotation protection, 5 poles, A coding, Pin 5 leading (Standard), without ventilation hole.
<b>Number of contacts</b>	5
<b>Color of housing</b>	black
<b>Product characteristics</b>	Oil resistance
<b>Classification</b>	
<b>Belden brand</b>	Lumberg-Automation
<b>Eclass-ID</b>	27260702
<b>Mechanical data</b>	
<b>Type of plug-in contact</b>	Male connector
<b>Design of housing</b>	straight
<b>Thread</b>	M12
<b>Design of electrical connection</b>	plug-in connection
<b>Coding of the M12 round plug connector</b>	A
<b>LED display present</b>	✘
<b>Connectable conductor cross-section multiple wire (without sleeve)</b>	max. 0.5 mm <sup>2</sup>
<b>connectable conductor cross-section multiple wire (without sleeve)</b>	0.5 mm <sup>2</sup>
<b>Environmental conditions</b>	
<b>Environmental temperature</b>	-25 °C ... 80 °C
<b>Pollution degree</b>	3
<b>Materials</b>	
<b>Contact bearer material</b>	PA
<b>Contact material</b>	CuZn
<b>Contact material - Surface refinement</b>	pre-nickeled and 0.8 microns gold-plated
<b>Sealing material</b>	FKM
<b>Electrical data</b>	
<b>Contact resistance</b>	≤ 5 mΩ
<b>Rated current In</b>	4 A at 40°C, UL and notice derating
<b>Nominal voltage</b>	60 V, encapsulated
<b>Rated voltage</b>	63 V
<b>Test voltage</b>	1.5 kV eff./60 s
<b>Insulation resistance</b>	> 1 GΩ
<b>Approvals</b>	
<b>Approvals</b>	UL

**Belden Deutschland GmbH**

Im Gewerbepark 2  
58579 Schalksmühle  
Germany  
Phone: +49 7127/14-1806  
E-Mail: [icos-sales@belden.com](mailto:icos-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular Metric Connectors](#) category:*

*Click to view products by [Lumberg](#) manufacturer:*

Other Similar products are found below :

[600X518037X](#) [6STD15PCR99B70A](#) [8R4000A16M020](#) [8R5000A16M005](#) [1200910002](#) [1203580030](#) [1200910008](#) [1200910011](#) [1300140094](#)  
[130203-0054](#) [1300140026](#) [1300150099](#) [RF-12S1N8A90DU](#) [1-3637-600-5205](#) [1612618](#) [21036836414](#) [8R4006A16M010](#) [8R5006A18A120](#)  
[1604232](#) [1R3006A20M005](#) [RF-12P1N8A80DU](#) [RF-12P1N8A90DU](#) [41-40011](#) [42-01015](#) [4-22279-4](#) [4-22281-1](#) [4-22284-9](#) [43-00113](#) [43-](#)  
[01088](#) [43-01203](#) [41-40013](#) [42-00008](#) [43-00343](#) [43-01032](#) [43-01162](#) [43-10000](#) [600X518050X](#) [SACC-DSI-FS-5P-PG9-L180 SC](#)  
[8R5006A16M020](#) [8R5006A16M005](#) [8R4000A16M010](#) [6-22279-3](#) [1605332](#) [N03FA03144](#) [1300140077](#) [43-01338](#) [XS2RD4265](#) [RSC 4/9](#)  
[XS2R-D426-1](#) [XS8A-0441](#)