

#### **M8 Field Attachable Connectors**


### RSMC | RKMC



#### Male, 3- and 4-Pole

Field attachable connector, M8 male connector 3- and 4-pole with threaded joint, assembling with solder connections.

#### **RSMC**






\*a O-Ring



#### Female, 3- and 4-Pole

Field attachable connector, M8 Female connector 3- and 4-pole with threaded joint, assembling with solder connections.

#### **RKMC**





- \*a O-Ring \*b Screw joint for cable

#### **Pin Assignments**

Face Views / M12, Male / Female

4 pole









## Be Certain with Belden



#### **M8 Field Attachable Connectors**

RSMC | RKMC

#### **Technical Data**

**Environmental** 

Degree of protection IP 67 / NEMA 6P

Operating temperature range RSMC: -25°C (-13°F) / +80°C (+176°F) RKMC: -40°C (-40°F) / +85°C (+185°F)

Mechanical

Housing / Molded body RSMC: CuZn, nickel-plated

RKMC: PBT

PA Insert

RSMC: CuZn, pre-nickeled and Contact

0.8 microns gold-plated RKMC: CuSn, gold-plated

CuZn, nickel-plated Receptacle shell 0-ring FKM (only RKMC)

Mode of connection Solder connection Connectable conductor RSMC: max. 0.34mm<sup>2</sup>

RKMC: max. 0.25 mm<sup>2</sup>

**Electrical** 

Contact resistance  $\leq$  5 m $\Omega$ Nominal current at 40°C

3 poles 60 V Nominal voltage

4 poles 30 V

Rated voltage 3 poles 63 V

4 poles 36 V

Test voltage RSMC:

3 poles 1.5 kV eff. / 60 s

4 poles 0.8 kV eff. / 60 s

Insulation resistance  $> 10^9 \,\Omega$ Pollution degree 3

Part Number		Pins	Cable Diameter Range	Characteristics
Male	Female			
RSMC 3	RKMC 3	3	Ø 3.5-5.0 mm	
RSMC 4	RKMC 4	4	Ø 3.5-5.0 mm	

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 XS2R-D426-1 XS8A-0441 859RD04-103R004