

M8-Receptacle Connectors In Accordance With IEC 61076-2-104


RSMEDG I RSMEDGN



Male, 8-Pole

Receptacle connector, M8 male connector for sensors, with combined snap-in/threaded joint, mounting hole for LED, short solder contacts, hollow contacts on solder side.

RSMEDG








Male, 3 and 4-Pole

Receptacle connector, M8 male connector for sensors, with housing of stainless steel, threaded joint, 4 light indicator windows, mounting hole for LED, short solder contacts, hollow contact on solder side.

RSMEDGN









*a ho**ll**ow *c cut out *d hole pattern in printed circuit board

Pin Assignments

Face Views







M8-Receptacle Connectors In Accordance With IEC 61076-2-104 RSMEDG | RSMEDGN

Technical Data

Environmental

Degree of protection	IP 67 / NEMA 6P
Operating temperature range	-25°C (-13°F) / +80°C (+176°F)

Mechanical

Housing / Molded body
Insert
Contact

Mode of connection Connectable conductor

Electrical

Contact resistance	\leq
Nominal current at 40°C	1.
Nominal voltage	30
Test voltage	0.
Insulation resistance	>
Pollution degree	3

F)

CuZn, nickel-plated PA CuZn, pre-nickeled and 0.8 microns gold-plated solder connection max. 0.14 mm²

 $5 \,\text{m}\Omega$.5 A 80 V .5 kV eff. / 60 s $10^9\,\Omega$

Part Number		Pins	Contact (soldering side)	Characteristics
RSMEDGN 3		3		
RSMEDGN 4		4		
	RSMEDG 8	8	hollow contact	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Lumberg manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-005413001400261300150099RF-12S1N8A90DU1-3637-600-52051612618210368364148R4006A16M0108R5006A18A12016042321R3006A20M005RF-12P1N8A80DURF-12P1N8A90DU41-4001142-010154-22279-44-22281-14-22284-943-0011343-0108843-0120341-4001342-0000843-0034343-0103243-0116243-10000600X518050XSACC-DSI-FS-5P-PG9-L180 SC8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-01338XS2RD4265RSC 4/9XS2R-D426-1XS8A-0441