



DESCRIPTION

The NSL-4132 is a light dependent resistor with sensitivity in the visible light region. The CdS photoconductive cell is on a TO-18 ceramic and the photocell surface is plastic encapsulated for moisture resistance.

FEATURES

- Passive resistance output
- Ceramic package

RELIABILITY

Contact Luna for recommendations on specific test conditions and procedures.

APPLICATIONS

- Industrial

ABSOLUTE MAXIMUM RATINGS

SYMBOL	MIN		MAX	UNITS	T _a = 23°C UNLESS NOTED OTHERWISE
Voltage (peak AC or DC)	-	-	80	V	-
Power Dissipation @25°C	-	-	50	mW	Derate linearly to at 75°C
Operating Temperature	-60	to	+75	°C	Non condensing
Storage Temperature	-60	To	+75	°C	-
Soldering Temperature	-	-	+260	°C	>2mm from case

Note:

1. Cells light adapted at 30 to 50 Ftc for 16 hrs. minimum prior to electrical tests

OPTO-ELECTRICAL PARAMETERS

T_a = 23°C UNLESS NOTED OTHERWISE

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Light Resistance	1 ftc., 2854° K (1)	18	30	42	KΩ
	100 ftc., 2854° K (1)	-	500	-	Ω
Dark Current	5 sec. after removal of test light	1.8	-	-	MΩ
Spectral Peak	-	-	550	-	nm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [luna optoelectronics manufacturer](#):

Other Similar products are found below :

[PDI-E804](#) [PDB-V615-2](#) [PDB-V601-1-25](#) [PDB-C110](#) [PDV-P9004](#) [PDB-C109](#) [PDB-V107](#) [PDB-C612-2](#) [PDB-C107](#) [SLSD-71N300](#) [PDV-P9103](#) [NSL-4960](#) [PDB-C609-2](#) [PDB-C158F](#) [PDV-P5002](#) [NSL-6910](#) [PDB-C613-2](#) [NSL-5150](#) [NSL-5510](#) [PDV-P8101](#) [PDV-P8005](#) [NSL-32SR2S](#) [PDV-P8107](#) [PDB-C160SM](#) [PDV-P5001](#) [PDV-P7002](#) [PDV-P9003-1](#) [PDV-P5003](#) [PDV-P9003](#) [NSL-5540](#) [NSL-32SR2](#) [PDV-P8006](#) [PDV-P8102](#) [PDB-C158](#) [PDV-P8001](#) [PDB-C171SM](#) [PDV-P9002](#) [PDV-P9200](#) [PDV-P9005](#) [NORPS-12](#) [APW-MW2-1210-010](#) [NSL-5152](#) [NSL-5162](#) [NSL-5112](#) [PDV-P9203](#) [NSL-6110](#) [NSL-06S53](#) [PDV-P9002-1](#) [PDB-C139](#) [PDV-P9006](#)