

E-Series Coupler 5 – 1000 MHz

Rev. V4


Features

- Coupling 10 dB Typical
- Surface Mount
- Tape and reel packaging available

Description

M/A-COM's EMDC-10-1 is a broadband coupler in a low cost, surface mount package. It offers low loss, good isolation, good input/output matching and exceptional coupling repeatability. Ideally suited for high volume cellular and wireless applications. Parts are packaged in tape & reel.

SM - 22 Package



Electrical Specifications: $T_A = 25^{\circ}C$, $Z_0 = 50\Omega^{1}$

Parameter	Test Conditions	Frequency	Units	Min	Тур	Max
RF Frequency	_	5 - 1000	MHz	_	_	_
Coupling	F _L —f _U	5 - 1000	dB	_	_	10 ±0.9
Main Line Loss	F _L —f _U	5 - 50 50 - 500 500 - 1000	dB dB dB	_ _ _	1.1 1.0 1.2	1.6 1.4 2.3
Directivity	F _L —f _U	5 - 50 50 - 500 500 - 1000	dB dB dB	17 15 10	20 19 17	_ _ _
Return Loss	F _L —f _U	5 - 1000	dB	14	17	

Absolute Maximum Ratings ¹

Parameter	Absolute Maximum		
RF Power	250 mW		
DC Current	30 mA		
Operating Temperature	-40°C to +85°C		
Storage Temperature	-55°C to +125°C		

Operation of this device above any one of these parameters may cause permanent damage.

Ordering Information

Part Number	Package
EMDC-10-1TR	Tape and Reel (2000 piece Reel)

typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

North America Tel: 800.366.2266
 India Tel: +91.80.43537383
 Europe Tel: +353.21.244.6400
 China Tel: +86.21.2407.1588

India Tel: +91.80.43537383 • China Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.

EMDC-10-1



E-Series Coupler 5 – 1000 MHz

Rev. V4

Pin Configuration

Pin No.	Function	
1	Input	
2	Ground	
3	Coupled	
4	External 50 Ohms	
5	Output	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by MACOM manufacturer:

Other Similar products are found below:

MAPDCC0001 MAPDCC0004 PD0409J5050S2HF 880157 HHS-109-PIN DC1417J5005AHF AFS14A30-2185.00-T3 AFS14A35-1591.50-T3 DS-323-PIN B39321R801H210 1A0220-3 JP510S LFB212G45SG8C341 LFB322G45SN1A504 LFL182G45TC3B746 SF2159E 30057 FM-104-PIN CER0813B MAPDCC0005 3A325 40287 41180 ATB3225-75032NCT BD0810N50100AHF BD2425J50200AHF C5060J5003AHF JHS-115-PIN JP503AS DC0710J5005AHF DC2327J5005AHF DC3338J5005AHF 43020 LFB2H2G60BB1C106 LFL15869MTC1B787 X3C19F1-20S XC3500P-20S 10013-20 SF2194E CDBLB455KCAX39-B0 TGL2208-SM, EVAL RF1353C PD0922J5050D2HF 1E1305-3 1G1304-30 B0922J7575AHF 2020-6622-20 TP-102-PIN TP-103-PIN BD1222J50200AHF