## MALLORY Mallory Sonalert Products, Inc. Part #: JR16-G-DLCT1 Revision: **Sales Outline Drawing** Α **Specifications:** Sound Level Category Loud Mode of Operation Continuous Voltage Rating 9 to 16 VDC Frequency 3900 ± 500 Hz Loudness @ 1M 80 to 85 dB(A) Typ. Sound Current Draw 25mA MAX LED Color **GREEN LED Current Draw** 25mA max **Total Max Current Draw** 50mA MAX **Housing Material** 6/6 Nylon, Color: Black Top Cap Material 6/6 Nylon, Color: Opaque White Storage Temperature -40° to +70° C Operating Temperature -30° to +60° C Mounting Recommended hole size is 22.5 mm. Knurled Nut The max recommended torque is 10 in-lbs. Gray, UL Style 21894, 300V, 105°C, 24AWG, Pb-Free Tinned Leads Cable Weight (Typical) 32 grams NEMA 12 Approved with use of included gasket. **Options** Please contact factory. **cUL** Recognized **ROHS Compliant Dimensions:** Inches (mm) 1.381 [35.07] 0.524 [13.31] 12±1" [305±25mm] 1.210 [30.73] Gasket M22 x 1.5 Thread <0.86 Maj. Dia. Knurl nut Connections: SOUND BLACK wire to Ground and ORANGE wire to Positive TOP BROWN wire to Ground and GREEN wire to Positive

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Piezo Buzzers & Audio Indicators category:

Click to view products by Mallory Sonalert manufacturer:

Other Similar products are found below:

6-4 68S1240-PA MBA-624 FDG06PSLLF FDG111PLF F/NRMB 24 BLACK LF PF-35N29WQ PFD-21A29W PFD-27A35PQ PL-21N30WQ PL-27A35PSQ PLD-21N30WQ PS-531Q PT-3534FP EBPT-401 B822B B/CP28/100DB/BLACK LF PB-1220PEQ S6109 SBM616PR SC110E SC2036ACP SC616N-2 SC628FW SC628MPG SC648D SCS045MD9DT3S FCM12PLF F/EB20P-DR LF F/SMD03A LF FSMD8585JSLF F/SU 21-02 LF F/TCW 12 WITH LABEL LF F/UCW 06 WITH LABEL LF PFD-27N36W PKM22EPPH40S1-B0 PKM35-4A0 PL-35N29WQ PS-552Q CM-5 REF-202 B/SE 128 RED LF KBS-20DA-7AS KBS-27DA-5C-105 LSC628ANR 03-810.001 RTO-1R07-001 PL-21N31PQ B/CP 28B BLACK LF