## MALLORY Mallory Sonalert Products,Inc. Part #: JR28-RYG-DLCT1 Revision: **Sales Outline Drawing** Α Specifications: Sound Level Category Loud Mode of Operation Continuous Voltage Rating 20 to 28 VAC/DC Frequency 3900 ± 500 Hz Loudness @ 1M 80 to 85 dB(A) Typ. Sound Current Draw 25mA MAX Stack Level **BOTTOM MIDDLE** TOP **LED Color GREEN** YELLOW **RED LED Current Draw** 60mA MAX 60mA MAX 25mA max **Total Max Current Draw** 170mA MAX Housing Material 6/6 Nylon, Color: Black Top Cap / Lens Material 6/6 Nylon, Color: Opaque White Storage Temperature -40° to +70° C **Operating Temperature** -30° to +60° C Mounting Recommended hole size is 22.5 mm. **Knurled Nut** The max recommended torque is 10 in-lbs. Cable Gray, UL Style 21894, 300V, 105°C, 24AWG, Pb-Free Tinned Leads Weight (Typical) 39 grams NEMA 12 Approved with use of included gasket. **Options** Please contact factory. cUL Recognized **ROHS Compliant Dimensions:** Inches (mm) 1.324 [33.63] 1.381 [35.07] 12±1" [305±25mm] 1.210 [30.73] M22 x 1.5 Thread <0.86 Mai. Dia. Knurl nut Connections: SOUND BLACK wire and ORANGE wire to Power BOTTOM BROWN wire and GREEN wire to Power MIDDLE BROWN wire and YELLOW wire to Power TOP BROWN wire and RED wire to Power

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Piezo Buzzers & Audio Indicators category:

Click to view products by Mallory Sonalert manufacturer:

Other Similar products are found below:

6-4 68S1240-PA MBA-624 FDG06PSLLF FDG111PLF F/NRMB 24 BLACK LF PF-35N29WQ PFD-21A29W PFD-27A35PQ PL-21N30WQ PL-27A35PSQ PLD-21N30WQ PS-531Q PT-3534FP EBPT-401 B822B B/CP28/100DB/BLACK LF PB-1220PEQ S6109 SBM616PR SC110E SC2036ACP SC616N-2 SC628FW SC628MPG SC648D SCS045MD9DT3S ESZ-25B-5-250B FCM12PLF F/EB20P-DR LF F/SMD03A LF FSMD8585JSLF F/SU 21-02 LF F/TCW 12 WITH LABEL LF F/UCW 06 WITH LABEL LF PFD-27N36W PKM22EPPH40S1-B0 PKM35-4A0 PL-35N29WQ PS-552Q CM-5 REF-202 B/SE 128 RED LF KBS-20DA-7AS KBS-27DA-5C-105 LSC628ANR 03-810.001 RTO-1R07-001 PL-21N31PQ