ALLORY Mallory Sonalert Products, Inc.				Part #: JT120-RYG-C		
Sales Outline Drawing				Revisio D		
ecifications:						
Stack Number:	1	2	3			
LED Color:	RED	YELLOW	GREEN			
Connection Wires:	Red and Brown	Yellow and Brown	Green and Brown			
LED Current Draw:	<210 mA	<230 mA	<190 mA			
Rated Voltage:			120 VAC	!		
Operating Voltage:			90-120 VAC			
Sound Level Category:	Loud	Loud	Loud		Loud	
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.5F	PPS)	Continuous for 5 sec the beep until reset	n 0
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to Green/Yellow wire	Black and Gray Wires wire connected Green/Yellow wi			d to
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max.		40mA Max.	
Loudness @ 1m:			80-85 dB(A) Typ.		•	_
Frequency:			2000 ± 500 Hz			_
Total Max Current:		<670mA with	all LED's and sound u	nit worki	ng	_
Operating Temperature:			-25° ~ +60°C			
Lens Color:			Opaque White			
Material:	ABS FR15U					
Mounting Method:	Direct Mount using 1/2" NPT Stainless Steel Pipe and Nut					
Weight Typical (g):			365			
NEMA 12:	Approved					
Options:		cUL Recogni	ease contact factory.		ROHS Com	
	7.4	ELLOW 188.9] Ø0.88 KNOCK FOR V	COUT ~			
OPERATION: CONNEC	T STACK COLOR WIF	RE TO POWER AND BRC	MDUNTING DIAGRAM	R.		

FOR DOUBLE PULSE, CONNECT GRAY & BLACK TO POWER AND PURPLE WIRE TO GREEN/YELLOW WIRE. FOR CONT/BEEP, CONNECT GRAY & BLACK TO POWER AND ORANGE & PURPLE TO GREEN/YELLOW WIRE.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by Mallory Sonalert manufacturer:

Other Similar products are found below:

LW1A-P1-GD LW1A-P1-W 01-931.3 01-152.025 73.362.4028.0 750-1520 9001OA120 A0142N5 A3DT-500Y AL6M-LK3-R AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-G APD106LN-S APN1126-G APS122DN-W ASLWLD-G ASLWLD-R ATN2100 AYLW4L-A 18-237.035 18-945 HW1A-L1-GD HW1A-P2-GL HW1X-BM411-R HW2A-L1-GL HW2A-P1-GD HWAZ1N-OB PA2100/2 PA2200/1 PA2SHIELD PAMR25 LA3P-1C03V-Y 96-923.5 A0244J2 LSPD-120A LSPD-1Y LSPD-6A LSPD-6DA LSPD-6DW LSPD-6DY LSPD-6R LSPD-6W 18-946 AL6H-LK3-A AL6H-P4-JW AL6M-LK1-MG AP8M155-G APD106LN-W