## Part #: MALLORY Mallory Sonalert Products, Inc. JT120-RYG-CSL Revision **Sales Outline Drawing** D Specifications: Stack Number: 3 LED Color: RED YELLOW **GREEN** Connection Wires: Red and Brown Yellow and Brown Green and Brown LED Current Draw: <210 mA <230 mA <190 mA 120 VAC Rated Voltage: Operating Voltage: 90-120 VAC Sound Level Category: Loud Loud Loud Loud Continuous for 5 sec then 0.1s Mode of Operation: Medium Pulse (5PPS) Double Pulse (0.5PPS) Continuous beep until reset Black and Grav Wires: Black and Grav Wires: Black and Gray wires; Orange Black and Gray Connection: Orange wire connected Purple wire connected to and Purple wires connected to Wires to Green/Yellow wire Green/Yellow wire Green/Yellow wire 40mA Max. 40mA Max 40mA Max. 40mA Max Sound Current Draw: Loudness @ 1m: 80-85 dB(A) Typ. Frequency: 2000 ± 500 Hz <670mA with all LED's and sound unit working **Total Max Current:** Operating Temperature: -25° ~ +60°C Opaque White Lens Color: Material: ABS FR15U Mounting Method: Stainless Steel Pole Weight Typical (g): 735 NEMA 12: Approved Options: Please contact factory. **ROHS Compliant** Dimensions: **cUL** Recognized Inches (mm) PATENT NUMBER(S) D898600 6.7 [169.8] -RED GREEN GASKET YELLOW -19.6 [497.6]-Ø0.57 [Ø14.6] for wires 2.4 (61.8) 2.04 [51.9] F0.39 [9.9] 0.95 [24.3] 0.95 [24.3] -2.7 [68.3] MOUNTING DIAGRAM TOP VIEW ED OPERATION: CONNECT STACK COLOR WIRE TO POWER AND BROWN WIRE TO POWER. SOUND OPERATION: CONNECT GRAY AND BLACK WIRES TO POWER FOR CONTINUOUS SOUND. FOR MEDIUM PULSE, CONNECT GRAY & BLACK TO POWER AND ORANGE WIRE TO GREEN/YELLOW WIRE FOR DOUBLE PULSE, CONNECT GRAY & BLACK TO POWER AND PURPLE WIRE TO GREEN/YELLOW WIRE. FOR CONT/BEEP, CONNECT GRAY & BLACK TO POWER AND ORANGE & PURPLE TO GREEN/YELLOW WIRE.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by Mallory Sonalert manufacturer:

Other Similar products are found below:

LW1A-P1-GD LW1A-P1-W 01-931.3 01-152.025 73.362.4028.0 750-1520 90010A120 A0142N5 A3DT-500Y AL6M-LK3-R AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-G APD106LN-S APN1126-G APS122DN-W ASLWLD-G ASLWLD-R ATN2100 AYLW4L-A 18-237.035 HW1A-L1-GD HW1A-P2-GL HW1X-BM411-R HW2A-L1-GL HW2A-P1-GD HWAZ1N-OB PA2100/2 PA2200/1 PA2SHIELD PAMR25 LA3P-1C03V-Y 96-923.5 A0244J2 LSPD-120A LSPD-1Y LSPD-6A LSPD-6DA LSPD-6DW LSPD-6DY LSPD-6R LSPD-6W AL6H-LK3-A AL6H-P4-JW AL6M-LK1-MG AP8M155-G APD106LN-W APN106L-O 21-931.9