

General Description

This IGBT is produced using advanced MagnaChip's Field Stop Trench IGBT Technology, which provides high switching series and excellent quality.

This device is for PFC, UPS & Inverter applications.

Features

- High Speed Switching & Low Power Loss
- $V_{CE(sat)} = 1.8 \text{ V}$ @ $I_C = 40\text{A}$
- $E_{off} = 0.35\text{mJ}$ @ $T_C = 25^\circ\text{C}$
- High Input Impedance
- $t_{rr} = 80\text{ns}$ (typ.) @ $dI_f/dt = 1000\text{A}/\mu\text{s}$
- Maximum junction temperature 175°C

Applications

- | | |
|---|---|
| <ul style="list-style-type: none"> ■ PFC ■ UPS ■ PV Inverter | <ul style="list-style-type: none"> ■ Welder ■ IH Cooker |
|---|---|



Parameter	Symbol	Rating	Unit
Collector-emitter voltage	V_{CE}	650	V
DC collector current, limited by T_{vjmax}	I_C	80	A
		40	A
Pulsed collector current, t_p limited by T_{vjmax}	I_{Cpuls}	160	A
Turn off safe operating area $V_{CE} \leqslant 600\text{V}$, $T_{vj} \leqslant 175^\circ\text{C}$	-	160	A
Diode forward current limited by T_{vjmax}	I_F	80	A
		40	
Diode pulsed current, t_p limited by T_{vjmax}	I_{Fpuls}	160	A
Gate-emitter voltage	V_{GE}	± 20	V
Power dissipation	P_D	375	W
		188	W
Short circuit withstand time $V_{CC} \leqslant 400\text{V}$, $V_{GE} = 15\text{V}$, $T_{vj} = 150^\circ\text{C}$ Allowed number of short circuits < 1000 Time between short circuits $\geqslant 1.0\text{s}$	t_{sc}	5	μs
Operating Junction temperature range	T_{vj}	-40~175	$^\circ\text{C}$
Storage temperature range	T_{stg}	-55~150	$^\circ\text{C}$
Soldering temperature Wave soldering 1.6 mm (0.063 in.) from case for 10s		260	$^\circ\text{C}$
Mounting torque, M3 screw Maximum of mounting processes: 3	M	0.6	Nm

Thermal Characteristic

Parameter	Symbol	Rating	Unit
Thermal resistance junction-to-ambient	$R_{\theta JA}$	40	$^\circ\text{C/W}$
Thermal resistance junction-to-case for IGBT	$R_{\theta JC}$	0.4	
Thermal resistance junction-to-case for Diode	$R_{\theta JCD}$	1.2	

Ordering Information

Part Number	Marking	Temp. Range	Package	Packing	RoHS Status
MSG40T65FL	40T65FL	-55~175°C	TO-247	Tube	Halogen Free

Electrical Characteristic ($T_{vj} = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Static Characteristic						
Collector-emitter breakdown voltage	BV_{CES}	$I_C = 2\text{mA}, V_{\text{GE}} = 0\text{V}$	650	-	-	V
Collector-emitter saturation voltage	$V_{\text{CE}(\text{sat})}$	$I_C = 40\text{A}, V_{\text{GE}} = 15\text{V}, T_{vj} = 25^\circ\text{C}$		1.95	2.4	V
		$I_C = 40\text{A}, V_{\text{GE}} = 15\text{V}, T_{vj} = 175^\circ\text{C}$		2.3		
Diode forward voltage	V_F	$V_{\text{GE}} = 0\text{V}, I_F = 40\text{A}$	$T_{vj} = 25^\circ\text{C}$	1.3	1.9	V
			$T_{vj} = 125^\circ\text{C}$	1.15		
			$T_{vj} = 175^\circ\text{C}$	1.1		
Gate-emitter threshold voltage	$V_{\text{GE}(\text{th})}$	$V_{\text{CE}} = V_{\text{GE}}, I_C = 0.58\text{mA}$	4.0	5.0	6.0	V
Zero gate voltage collector current	I_{CES}	$V_{\text{CE}} = 650\text{V}, V_{\text{GE}} = 0\text{V}$	$T_{vj} = 25^\circ\text{C}$	-	-	40
			$T_{vj} = 175^\circ\text{C}$	-	-	1000
Gate-emitter leakage current	I_{GES}	$V_{\text{GE}} = 20\text{V}, V_{\text{CE}} = 0\text{V}$	-	-	± 100	nA
Transconductance	g_{fs}	$V_{\text{CE}} = 20\text{V}, I_C = 40\text{A},$		17.0		S
Dynamic Characteristic						
Total gate charge	Q_g	$V_{\text{CE}} = 520\text{V}, I_C = 40\text{A}, V_{\text{GE}} = 15\text{V}$	-	219		nC
Gate-emitter charge	Q_{ge}		-	26		
Gate-collector charge	Q_{gc}		-	115		
Input capacitance	C_{ies}	$V_{\text{CE}} = 25\text{V}, V_{\text{GE}} = 0\text{V}, f = 1\text{MHz}$	-	2818	-	pF
Reverse transfer capacitance	C_{res}		-	131	-	
Output capacitance	C_{oes}		-	209	-	
Internal emitter inductance measured 5mm (0.197 in.) from case	L_E		-	13.0	-	nH
Short circuit collector current Max. 1000 short circuits Time between short circuits: $\geq 1.0\text{s}$	$I_{\text{C}(\text{SC})}$	$V_{\text{GE}} = 15\text{V}, V_{\text{CC}} = 400\text{V}, t_{\text{sc}} \leq 5\mu\text{s}, T_{vj} = 150^\circ\text{C}$	-	180	-	A
Switching Characteristic						
Turn-on delay time	$t_{\text{d}(\text{on})}$	$V_{\text{GE}} = 15\text{V}, V_{\text{CC}} = 400\text{V}, I_C = 40\text{A}, R_G = 7.9\Omega, \text{Inductive Load, } T_{vj} = 25^\circ\text{C}$	-	58	-	ns
Rise time	t_r		-	54	-	
Turn-off delay time	$t_{\text{d}(\text{off})}$		-	245	-	
Fall time	t_f		-	40	-	
Turn-on switching energy	E_{on}		-	1.15	-	mJ
Turn-off switching energy	E_{off}		-	0.35	-	
Total switching energy	E_{ts}		-	1.50	-	
Reverse recovery time	t_{rr}	$I_F = 40\text{A}, dI_F/dt = 1000\text{A}/\mu\text{s}, T_{vj} = 25^\circ\text{C}$	-	80	-	ns
Reverse recovery current	I_{rr}		-	25	-	A
Reverse recovery charge	Q_{rr}		-	1.0	-	μC
Rate of fall of reverse recovery current during t_b	dI_{rr}/dt		-	-950	-	$\text{A}/\mu\text{s}$

Switching Characteristic

Turn-on delay time	$t_{d(on)}$	$V_{GE} = 15V, V_{CC} = 400V,$ $I_c = 40A, R_G = 7.9\Omega,$ Inductive Load, $T_{vj} = 175^\circ C$	-	61	-	ns
Rise time	t_r		-	60	-	
Turn-off delay time	$t_{d(off)}$		-	260	-	
Fall time	t_f		-	38	-	
Turn-on switching energy	E_{on}	$I_F = 40A, di_F/dt = 1000A/\mu s,$ $T_{vj} = 175^\circ C$	-	1.80	-	mJ
Turn-off switching energy	E_{off}		-	0.38	-	
Total switching energy	E_{ts}		-	2.18	-	
Reverse recovery time	t_{rr}		-	145	-	ns
Reverse recovery current	I_{rr}	$I_F = 40A, di_F/dt = 1000A/\mu s,$ $T_{vj} = 175^\circ C$	-	44	-	A
Reverse recovery charge	Q_{rr}		-	3.2	-	nC
Rate of fall of reverse recovery current during t_b	di_{rr}/dt		-	-680	-	A/ μs




Fig.1 Typical Output Characteristics($T_j=25^\circ\text{C}$)




Fig.2 Typical Output Characteristics($T_j=175^\circ\text{C}$)




Fig.3 Typical Transfer Characteristics




Fig.4 Typical Collector-Emitter Saturation Voltage - Junction Temperature




Fig.5 Diode Forward Characteristics




Fig.6 Diode Forward-Junction Temperature




Fig.7 Threshold Voltage-Junction Temperature




Fig.8 Typical Capacitance




Fig.9 Typical Gate Charge




Fig.10 Typical Turn on-Collector Current




Fig.11 Typical Turn off-Collector Current




Fig.12 Switching Loss-Collector Current




Fig.13 Turn on Characteristics-Gate Resistance




Fig.14 Turn off Characteristics-Gate Resistance




Fig.15 Switching Loss-Gate Resistance




Fig.16 Turn on Characteristics -Junction Temperature




Fig.17 Turn off Characteristics -Junction Temperature




Fig.18 Switching Loss-Junction Temperature




Fig.19 Switching Loss-Collector Emitter Voltage




Fig.20 Reverse Recovery Time
-Diode current slope




Fig.21 Reverse Recovery Charge
-Diode Current Slope




Fig.22 Reverse Recovery Current
-Diode current slope




Fig.23 Rate of fall of reverse recovery current
-Diode Current Slope




Fig.24 Forward Bias Safe Operating Area




Fig.25 Typical Short Circuit Collector Current




Fig.26 Typical Short Circuit Withstand Time




Fig.27 Case Temperature-Collector Current




Fig.28 Power Dissipation-Case Temperature




Fig.29 IGBT Transient Thermal Impedance





Fig.30 FRD Transient Thermal Impedance

Physical Dimension

TO-247

Dimensions are in millimeters, unless otherwise specified



Dimension	Min(mm)	Max(mm)
A	4.70	5.31
A1	2.20	2.60
A2	1.50	2.49
b	0.99	1.40
b1	2.59	3.43
b2	1.65	2.39
c	0.38	0.89
D	20.30	21.46
D1	13.08	-
E	15.45	16.26
E1	13.06	14.02
E2	4.32	5.49
e	5.45BSC	
L	19.81	20.57
L1	-	4.50
ΦP	3.50	3.70
Q	5.38	6.20
S	6.15BSC	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MASPOWER manufacturer:

Other Similar products are found below :

[MSG80N60FQC](#) [MS8N120FE](#) [PWM815YBN](#) [MS8N120FC](#) [MS6N120FE](#) [MS60N60HGC1](#) [ESTF60SS120US](#) [MSG40T120FQC](#)
[MSG50T120FQW](#) [MS5N100FT](#) [ESTF15SS135UC](#) [MS170N25HGF4](#) [MS5N170FC](#) [EST100BN120SN](#) [EST60BN120SN](#) [MS50N100HGF4](#)
[MS170N65HGF4](#) [MSG50N350FH](#) [MS8N100FS](#) [ESTF8SS120C](#) [MS30N100HGC0](#) [MSG120T65HLC1](#) [ESTF80D22U](#) [MS3N100HGT1](#)
[EST100BN60SN](#) [MSG60T65HHC0](#) [MSG20T65FQC](#) [MS12N100FS](#) [MSG40T65HHC0](#) [MS120N10FT](#) [MS50N20FC](#) [MS38N65FCC](#)
[MSG40T65HPC0](#) [MSG100T65HLB3](#) [MSG50T65FQC](#) [MS12N100FC](#) [MS12N120HJC0](#) [MS10N120HGC0](#) [MS6N100FE](#) [MS15N120HGC0](#)
[MS100N20IDC0](#) [MS15N100HGC0](#) [MS3N100HGD1](#) [MS140N30HGB3](#) [ESTF15SS120C](#) [MS120N15FB](#) [MS10N100HGC0](#) [MS8N100FE](#)
[MSG25T120FQC](#) [MS4N1350W](#)