





注：本板为禁止运输、复制、翻印文件，以及用其内容进行交流



REV	ECN NO.	CONTENT	CHK	DATE

NOTES1:  
UL Standard  
1.Rating voltage/current: 300V/8A  
2.withstanding voltage: AC2000V/1Min  
3.Torque value: M2.0, 1.77Lb.in  
4.Wire range: 28~16AWG

IEC Standard

1. Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	2.5KV
Rate Voltage(V)	250V
Rate Current(A)	7A

2. Torque value: M2, 0.2Nm  
3.wire range: 0.5~1.5mm<sup>2</sup>

NOTES2:  
1.Housing: PA66 (UL94V-0)  
2.Cover: PA66 (UL94V-0)  
3.Cage: Brass (Ni Plated)  
4.Clamp: Copper alloy (Ni Plated)  
5.Screw: Steel (M2.0,Zn Plated)

NOTES3:  
1.Pitch: 3.5mm Poles: 02-24P  
2.Stripping length: 6-7mm  
3.Operating temperature: -40℃~+105℃  
4.RoHS Compliance

How to order  
MX15EDGK - 35 - XXP - XXXX - XX - X - X

产品型号 间距 颜色 极数

灰色:GY 橙色:OE 01:常规颜色  
蓝色:BU 红色:RD 定制颜色  
黑色:BK 透明色:TT  
绿色:GN 黄色:YW  
透明色:TT 白色:WE

A-Z其他定制  
0-Y一字螺丝  
1-S十字螺丝  
2-PS平头十字螺丝  
Cu:铜方块  
Fe:铁方块

Pitch Range In mm	Nominal Dimension Range In mm						Over 150	0.1/10
	Over 6	Over 10	Over 24	Over 30	Over 60	Over 100		
TO 6	TO 10	TO 24	TO 30	TO 60	TO 100	TO 150	∠	
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	CHK	DATE	22.09.14	UNITS	MM
CHK	DATE	SCALE	1:1	SHEET/OF	A4
APP	DATE	NAME	MX15EDGK-3.5-XXP		

CXI MAXU ELECTRONICS CO.,LTD  
MAXU 慈溪市迈旭电子有限公司

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pluggable Terminal Blocks](#) category:*

*Click to view products by [MAX](#) manufacturer:*

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [860505](#) [860516](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP03-3,50](#)  
[PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFP03110](#) [ELFP10210](#) [ELFT07250](#) [ELVD12100](#) [ELVF09400](#)  
[ELVP03100](#) [ELXH071G0E](#) [1700410](#) [1746952](#) [1760336](#) [1800272](#) [1809474](#) [1855000000](#) [19346](#) [1946309](#) [1950227](#) [1973592](#) [19892](#)  
[25.320.4053.1](#) [25.320.4553.9](#) [25.320.4753.1](#) [25.320.5453.1](#) [25.340.0353.1](#) [25.340.1053.1](#) [25.345.3553.0M001](#) [25.640.3553.1](#) [SH02-5,08](#)  
[SH06-3,81](#) [SH08-5,08](#) [SH08-5,08-K](#) [SH12-5,08](#) [SHS04-5,00](#) [30.303](#) [30.305](#) [30.306](#)