





注：本板为禁止运输、复制、翻印文件，以及用其内容建设交流



REV	ECN NO.	CONTENT	CHK	DATE

NOTES:

UL Standard

Use group	B	C	D
Rated Current	5A	/	/
Rated Voltage	150V	/	/

- 1. Torque value: M1.6, 0.89LbIn
- 2. Torque value: M1.6, 0.89LbIn
- 3. Wire range: 26~20AWG

IEC Standard

Pollution Degree	3	2	2
Overvoltage Category	III	III	II
Rate Impulse Voltage(kV)	1.5kV	2.5kV	2.5kV
Rate Voltage(V)	100V	160V	320V
Rate Current(A)	5A	5A	5A

- 2. Torque value: M1.6, 0.1Nm
- 3. wire range: 0.2~0.5mm²

NOTES2:


- 1.Housing: PA66 (UL94V-0)
- 2.Cover: PA66 (UL94V-0)
- 3.Cage: Brass (Ni Plated)
- 4.Clamp: Copper alloy (Ni Plated)
- 5.Screw: Steel (M1.6,Zn Plated)

NOTES3:

- 1.Pitch: 2.54mm Poles: 02-24P
- 2.Stripping length: 5-6mm
- 3.Operating temperature: -40℃~+105℃
- 4.RoHS Compliance

How to order

MXZEDGK - 254 - XXP - XXXX - XX - X - X



Pitch Range In mm

Over	Nominal Dimension	Range
6	In mm	-
10		0.1/10
TO		∠

Over	Nominal Dimension	Range
6	In mm	-
10		0.1/10
TO		∠

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	CHK	DATE	UNITS	MM	1/1
APP	DATE	SCALE	A4		
CIXI MAIXU ELECTRONICS CO.,LTD					MXZEDGK-2.54-XXP
东莞市迈旭电子有限公司					DWGNO.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [MAX](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [860505](#) [860516](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP03-3,50](#)
[PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFP03110](#) [ELFP10210](#) [ELFT07250](#) [ELVD12100](#) [ELVF09400](#)
[ELVP03100](#) [ELXH071G0E](#) [1700410](#) [1746952](#) [1760336](#) [1800272](#) [1809474](#) [1855000000](#) [19346](#) [1946309](#) [1950227](#) [1973592](#) [19892](#) [2-](#)
[1546857-6](#) [25.320.4053.1](#) [25.320.4553.9](#) [25.320.4753.1](#) [25.320.5453.1](#) [25.340.0353.1](#) [25.340.1053.1](#) [25.345.3553.0M001](#) [25.640.3553.1](#)
[SH02-5,08](#) [SH06-3,81](#) [SH08-5,08](#) [SH08-5,08-K](#) [SH12-5,08](#) [SHS04-5,00](#) [30.303](#) [30.305](#)