





注：本板为禁止运输、复制、编辑文件，以及用其内容进行交流



NOTES1:

UL Standard

1. Use group	B	C	D
Rated Current	15A	-	10A
Rated Voltage	300V	-	300V

3. Torque value: M2.5, 3.54Lb.in
 4. Wire range: 28~12AWG
 IEC Standard


1. Pollution Degree	3	2	2
Overvoltage Category	III	III	II
Rate Impulse Voltage(KV)	/	4.0KV	/
Rate Voltage(V)	/	320V	/
Rate Current(A)	/	12A	/

2. Torque value: M2.5, 0.4Nm
 3. wire range: 10~2.5mm²
 NOTES2:

1. Housing: PA66 (UL94V-0)
 2. Cover: PA66 (UL94V-0)
 3. Cage: Brass (Ni Plated)
 4. Clamp: Copper alloy (Ni Plated)
 5. Screw: Steel (M2.5, Zn Plated)

- NOTES3:
1. Pitch: 5.08mm Poles: 02-24P
 2. Stripping length: 7-8mm
 3. Operating temperature: -40℃~+105℃
 4. RoHS Compliance

How to order



Pitch	Range	In	Nominal Dimension	Range								
mm			In mm									
Over	6	Over	10	Over	30	Over	60	Over	100	Over	150	
TO	10	TO	24	TO	30	TO	60	TO	100	TO	150	
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°				

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	CHK	DATE	SCALE	SHEET/OF	1/1
APP	DATE		1:1	A4	
CIXI MAIXU ELECTRONICS CO.,LTD			MX2EDGKBM-5.08-XXP		
MAIXU 慈溪市迈旭电子有限公司			DWGNO.		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Terminal Blocks](#) category:

Click to view products by [MAX](#) manufacturer:

Other Similar products are found below :

[MBE-1512](#) [MBE-1520](#) [MBE-154](#) [MBE-156](#) [MBES-156](#) [MH-2512](#) [MHE-132](#) [MHE-163](#) [MI-254 \(35\)](#) [MI-272](#) [MPT-275](#) [15602-04-08-21](#)
[ELM10110G](#) [BA311TU](#) [BA411SU](#) [MV-254-D](#) [MV-255](#) [MV-493](#) [MVE-252](#) [MVE-253](#) [MVEB-153](#) [1705142](#) [1712417](#) [1713088](#) [1745195](#)
[1760594](#) [1-796689-8](#) [1800114](#) [20020314-C121B01LF](#) [KP03215000J0G](#) [KP04215000J0G](#) [S451](#) [29.007](#) [29.116](#) [30.204](#) [30.503](#) [30.756](#)
[30.853](#) [996750](#) [1710052](#) [1777707](#) [1-796692-3](#) [20020316-G071B01LF](#) [20020327-C061B01LF](#) [29590](#) [30.652](#) [30.710](#) [30.754](#) [30.757](#) [32.058](#)