

生产作业书

已量产

客户编码		发行日期	2020-04-09			
客户物料编码		客户规格型号	5*12-4uH 0.5线			
祥如物料编码	XR5*12-4R0K-A	祥如规格型号	XR5*12-4R0K-A			
送样数量	50PCS	送样日期	2020-04-07			
外观尺寸mm			A	6.5 MAX		
			B	17.0±1.0		
			C	0.6±0.1		
			D	62.0±2.0		
			标识			
	原理图					
绕线结构表						
绕组	起始	结束	漆包线	圈数	绕制方式	
N1	S	F	2UEW-0.50mm	13.6TS	圈数参考 平整密绕	
注意事项						
1、产品磁芯中柱须使用3.0mm。 2.使用少字套管。						
测试项目	电性范围	测试条件	测试仪器	参考值		
电感量L	4uH±10%	at 25℃ 1KHz/0.25V	HK-100	4.1		
直流电阻DCR	40mΩ MAX	at 25℃ 1KHz/0.25V	HK-100	21		
饱和电流Isat	L ≥ L0*90%	at 25℃ DC4A 1KHz/0.3V	TH2829A			
物料	规格型号	备注	生产厂家	用量		
磁芯	C5 DRWW5*12 3*8		JIACHENG	K		
无铅锡	无铅锡条		SONGBEN	Kg		
漆包线	2UEW(155度)		GANYUE	Kg		
套管	Φ5*18mm UL黑色扁管		XINGQI	m		
接脚胶	FK661 黑胶 无卤		QI FU	Kg		
导针	0.60mm CP线		BAICHUAN	Kg		
作业流程						
产品包装						
包装代码						
包装标识						
包装物料						
包装尺寸						
包装说明						
标识示意图			包装示意图			
		制表	黄禾香			
		审核	钟传根			
		确认	黄传根			

文件编号： CRS-20200426-3286

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [MaxLinear](#) manufacturer:

Other Similar products are found below :

[CR32NP-100KC](#) [70F224AI](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#)
[PE-53601NL](#) [PE-53602NL](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2-R47-R](#) [HC8-1R2-R](#)
[HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-4R7M](#) [RCP1317NP-391L](#) [DH2280-4R7M](#) [DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-](#)
[RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#)
[1812LS-224XJ](#) [1812LS-563XJ](#) [1812LS-683XJ](#) [1812LS-824XJ](#) [NIN-FB101JTR110F](#) [NIN-FB471JTR62F](#) [NIN-FC1R5JTR220F](#) [NIN-](#)
[HCR15JTRF](#) [NIN-HCR33JTRF](#) [NIN-HDR22JTRF](#) [NIN-HDR82JTRF](#) [NIN-HK2N7STRF](#) [NIN-PA150KTR370F](#) [NIN-PB100KTR550F](#)