




## **Description**

Our patch antenna offerings are perfect for projects with a smaller scope and budget for which high-performance and lower weight is not a primary factor for consideration for the antenna. They are ideal for less demanding applications where extreme performance and battery life can be sacrificed at the expense of device cost. This dual band GPS/GLONASS antenna is designed for various vehicle tracking, oil & gas and M2M applications though it is used for a variety of commercial and industrial applications. It features a low noise figure and high-linearity LNA. The interface connector is available in SMA, TNC, or other options.

## **Mechanical Specifications**

| Parameter      | Design Specifications     |
|----------------|---------------------------|
| RF connector   | SMA, TNC, or other        |
| Cable          | RG174 / 3 meters or other |
| Antenna weight | 70 grams (max)            |





dimensions are in mm

## **Electrical Specifications**

| Parameter              | Design Specifications       |
|------------------------|-----------------------------|
| Frequency              | 1590 MHz                    |
| Polarization           | RHCP                        |
| DC voltage             | 2.5 to 5 V                  |
| DC current             | 11 mA (max)                 |
| Total system peak gain | 30 dB @ 2.5 V / 32 dB @ 5 V |
| Axial ratio            | 1 dB (min)                  |
| Bandwidth (-1db)       | 20 MHz                      |
| VSWR                   | 1.5:1                       |
| Impedance              | 50 Ohm                      |
| Operating temp.        | from -40°C to 85°C          |

#### **Features**


- · GPS/GLONASS coverage
- Active LNA circuitry
- · Waterproof housing
- · Compact size
- Custom tuning

# **Applications**

- · Vehicle and fleet tracking
- · Military & security
- · Asset tracking
- · Embedded applications
- Oil & gas industries
- Navigation devices
- · Mining equipment
- · LBS & M2M applications
- · Handheld devices
- Law enforcement

## Realized gain plot

measured at 1590 MHz on a 127X127mm  $\,$  ground plane (E plane, 2.5 V)





# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Maxtena manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF EXB144SM C37 MAF94051 GD35-17P-NF P1744 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352