


- Features :
  - 2:1 wide input range
  - 1000VDC I/O isolation
  - Built-in remote ON/OFF control
  - Built-in EMI filter
  - Protections: Short circuit / Overload
  - Cooling by free air convection
  - Single in line package
  - 100% full load burn-in test
  - Low cost / High reliability
  - Modified models available: output 3.3V/9V
  - 2 years warranty



SPECIFICATION

ORDER NO.	SPB03E-05	SPB03A-05	SPB03B-05	SPB03C-05	SPB03E-12	SPB03A-12	SPB03B-12	SPB03C-12	SPB03E-15	SPB03A-15	SPB03B-15	SPB03C-15
OUTPUT	DC VOLTAGE				12V				15V			
	CURRENT RANGE				25 ~ 250mA				20 ~ 200mA			
	RATED POWER				3W							
	RIPPLE & NOISE (max.) Note.2				50mVp-p				60mVp-p			
	LINE REGULATION Note.3				±0.5%							
	LOAD REGULATION Note.4				±0.5%							
	VOLTAGE ACCURACY				±2.0%							
	SWITCHING FREQUENCY				100KHz min.							
INPUT	VOLTAGE RANGE											
	E: 4.5 ~ 9VDC A: 9 ~ 18VDC B: 18 ~ 36VDC C: 36 ~ 72VDC											
	EFFICIENCY (Typ.)											
	74% 73% 77% 78% 76% 80% 80% 79% 75% 80% 80% 82%											
	DC CURRENT											
	Full load E: 810mA A: 340mA B: 165mA C: 85mA No load E: 110mA A: 40mA B: 20mA C: 10mA											
FILTER												
Capacitor Type												
REMOTE CONTROL												
Power ON : R.C. ~ -Vin < 1VDC or open ; Power OFF : R.C. ~ -Vin > 4VDC												
PROTECTION												
Fuse recommended												
PROTECTION (Note. 5)	OVERLOAD											
	150 ~ 250% rated output power Protection type : Recovers automatically after fault condition is removed											
	SHORT CIRCUIT											
	All output equipped with short circuit Protection type : Recovers automatically after fault condition is removed											
ENVIRONMENT	WORKING TEMP.											
	-40 ~ +85°C (Refer to "Derating Curve")											
	WORKING HUMIDITY											
	20% ~ 90% RH non-condensing											
	STORAGE TEMP., HUMIDITY											
-40 ~ +105°C, 10 ~ 95% RH												
TEMP. COEFFICIENT												
±0.05% / °C (0 ~ 50°C)												
VIBRATION												
10 ~ 500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes												
SAFETY	SAFETY STANDARDS											
	EAC TP TC 004 approved											
	WITHSTAND VOLTAGE											
	I/P-O/P:1KVDC											
	ISOLATION RESISTANCE											
	I/P-O/P: 100M Ohms / 500VDC / 25°C / 70% RH											
ISOLATION CAPACITANCE												
80pF max.												
EMC EMISSION												
Compliance to EN55032 Class B, FCC part 15 Class B, EAC TP TC 020												
EMC IMMUNITY												
Compliance to EN61000-4-2,3,4,5,6,8 light industry level, criteria A, EAC TP TC 020												
OTHERS	MTBF											
	600Khrs min. MIL-HDBK-217F(25°C)											
	DIMENSION											
21.8*9.2*11.1mm or 0.86"*0.36"*0.44" inch (L*W*H)												
WEIGHT												
4.8g												


■ Mechanical Specification



■ Pin Configuration

Pin No.	Output
1	-Vin
2	+Vin
3	R.C.
5	N.C.
6	+Vout
7	-Vout
8	N.C.

■ Derating Curve



NOTE

- All parameters are specified at normal input, rated load, 25°C 70% RH ambient.
  - Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
  - Line regulation is measured from low line to high line at rated load.
  - Load regulation is measured from 10% to 100% rated load.
  - Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.
- ※ Product Liability Disclaimer : For detailed information, please refer to <https://www.meanwell.com/serviceDisclaimer.aspx>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Isolated DC/DC Converters](#) category:*

*Click to view products by [Mean Well](#) manufacturer:*

Other Similar products are found below :

[ESM6D044440C05AAQ](#) [FMD15.24G](#) [PSL486-7LR](#) [Q48T30020-NBB0](#) [JAHW100Y1](#) [SPB05C-12](#) [SQ24S15033-PS0S](#) [19-130041](#) [CE-1003](#)  
[CE-1004](#) [GQ2541-7R](#) [RDS180245](#) [MAU228](#) [J80-0041NL](#) [DFC15U48D15](#) [XGS-0512](#) [XGS-1205](#) [XGS-1212](#) [XGS-2412](#) [XGS-2415](#) [XKS-](#)  
[1215](#) [06322](#) [NCT1000N040R050B](#) [SPB05B-15](#) [SPB05C-15](#) [L-DA20](#) [DCG40-5G](#) [QME48T40033-PGB0](#) [XKS-2415](#) [XKS-2412](#) [XKS-2405](#)  
[XKS-1212](#) [XKS-1205](#) [XKS-0515](#) [XKS-0505](#) [XGS-2405](#) [XGS-1215](#) [XGS-0515](#) [PS9Z-6RM4](#) [73-551-5038I](#) [AK1601-9RT](#) [VI-R5022-](#)  
[EXWW](#) [PSC128-7iR](#) [RPS8-350ATX-XE](#) [DAS1004812](#) [VI-LJ11-iz](#) [PQA30-D24-S24-DH](#) [VI-M5F-CQ](#) [VI-LN2-EW](#) [VI-PJW01-CZY](#)