

# TDR2000/3 and TDR2010

## Advanced Dual Channel TDR



- **Comprehensive Dual Channel capability with dual aspect display.**
- **AUTO set up mode for instant use.**
- **Ultra fast pulse for near end fault identification.**
- **AutoFind guidance to potential fault.**
- **IP54 rating offers real life working.**
- **Designed for use on all metallic paired cables.**

### DESCRIPTION

The Megger® TDR2000/3 and TDR2010 are state of the art, dual channel, high resolution, compact Time Domain Reflectometers with a colour screen for locating faults on paired metallic cables.

Both TDRs have a minimum resolution of 0.1m/0.3ft and a 20km/60kft maximum range depending on the velocity factor selected and the cable type.

Five output impedances are available (25, 50, 75, 100, 125 ohms) and an auto impedance matching feature. The velocity factor can be set between 0.2 and 0.99 to meet any cable test requirements.

### FEATURES AND BENEFITS

The TDR20xx series has a large, high resolution, colour, WVGA display with easy set up features. Directional control buttons, together with soft keys, provide intuitive and easy operation for the user.

An AUTO selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the TDR trace. The ability to manually override the auto function allows fine tuning to enable identification of hard to determine faults.

Dual trace and dual cursor capabilities allow full flexibility, giving the operator full control and instant indication of distance between two points.

A trace comparison feature also allows close examination between trace conditions. Extra high resolution together with a white-light backlight, user definable tones and colour give the graphical display a vibrance, aiding the user in identifying key events on the trace.

### Trace Storage

100 internal trace memories provide for the storage and recall of test results. The traces can be recalled to the display for analysis or compared with an active display to aid in fault location.

Alternatively the stored results can be downloaded to a computer, via the USB port, using the TraceXpert software and USB lead provided.

### Fault identification

Megger's own built-in AutoFind mode allows for speedy identification of faults. One press of the AutoFind key automatically adjusts the range and gain, and positions the cursor to the first major event on the cable. Press the AutoFind key again and the cursor will jump to the next detected disturbance.

For those who wish to maintain manual control, manual operation allows full override access to refine the response for easy fault identification.

### Trace Tagging

The addition of a trace tagging function on the TDR2010 allows the user to maintain accurate records of circuit details against every saved result. This is retrieved into the TraceXpert software for inclusion in the master record and for use on reports.

### TraceXpert PC software

The TDR2000/3 and TDR2010 come complete with the Megger TraceXpert software which gives full control over downloading, reporting and uploading of saved trace results. Designed around a database and programmed for ease of use and simplicity, TraceXpert offers the ideal application for all your data processing requirements.

## Models

The TDR20xx series is available in 3 models.

### TDR2000/3

A fully featured high resolution TDR with backlit colour display and powered by Li-ion rechargeable battery batteries. This model comes complete with 2 pairs of mini-clip Test Leads.

### TDR2000/3P

The same as the TDR2000/3 but with Dual fused test leads replacing the mini-clip leads

### TDR2010

The same as the TDR2000/3 but with Trace Tagging and additional Colour Scheme selection.

## BENEFITS

- Backlit graphics colour LCD (800x480)
- Adjustable display contrast
- Resolution to 0.1 m
- AutoFind guide to potential fault location
- 100 trace on board memory
- USB connection to PC allowing upload and download of traces
- "TraceXpert" PC software analysis tool
- For use on Telecom TNV-3 circuit, or 150V CAT IV power circuits
- Power blocking filter built-in
- Environmental protection to IP54
- Selectable output impedance (25, 50, 75,100 and 125Ω)
- 2ns pulse for near end fault location
- AUTO option selecting gain and pulse for each range
- AUTO option matches output impedance to cable
- Display distance in metres or feet
- Li-ion rechargeable battery (12 hours typical life)

## SPECIFICATIONS

Except where otherwise stated, this specification applies at an ambient temperature of 20°C.

### GENERAL

#### Range

Up to 20000m with a minimum resolution of 0.1m

m	ft	ns
10	30	125
25	75	250
50	150	500
100	300	100
250	750	2500
500	1500	5000
1000	3000	10000
2500	7500	25000
5000	15000	50000
10000	30000	100000
20000	60000	200000

#### Accuracy

±1% of range ±1 pixel at 0.67 VF  
[Note - The measurement accuracy is for the indicated cursor position only and is conditional on the velocity factor being correct.

#### Resolution

1% of range

## Input protection

This instrument complies with IEC61010-1 to protect the user in the event of connection to live systems up to 150 V CAT IV. This instrument is designed for use on de-energised systems but fused leads must be used if the potential voltage between terminals could exceed 300 V.

## Output pulse

Up to 20 volts peak to peak into open circuit. Pulse widths determined by range and cable.

## Gain

Set for each range with user selectable steps (in Manual operating mode)

## Velocity factor

Variable from 0.2 to 0.99 in steps of 0.01

## TX null

Automatic

## Power down

User programmable auto power off timer 1, 5, 10 mins or never

## Battery

Li-ion rechargeable battery

## Battery charge time

6 hours at 0 °C to 40 °C

## Battery life

12 hours typical

## Safety

This instrument complies with IEC61010-1 for connection to live systems up to 150 V CAT IV or 300 V CAT III. Fused leads must be used if the voltage between the terminals exceeds 300 V. Compliant with EN60950-1, EN61010-3, UN38.3 and EN62133

## EMC

Complies with Electromagnetic Compatibility Specifications (Light industrial) BS EN 61326-1, with a minimum performance of 'B' for all immunity tests.

## MECHANICAL

### IP rating

The instrument is designed for use indoors or outdoors and is rated to IP54.

### Case

ABS

### Dimensions

290 mm (11.4 in) x 190 mm (7.5 inches) x 55 mm (2.2 inches)

### Weight

1.7kg (3.8lbs)

### Connectors

Four 4mm-safety terminals and two F connectors. Other standard push on adapters will fit the TDR20xx series.

### Test lead

1.5 metres long consisting of 2 x 4mm shrouded connector to miniature crocodile clips (TDR2000/3 and TDR2010) or 1.5 metre fused leads (TDR2000/3P)

**Display** 800 x 480 pixel colour graphics LCD, viewable in external environments.  
**Colour Schemes**  
 Selectable - TDR2000/3 x2 TDR2010 x8  
 Custom - TDR2000/3 x1 TDR2010 x2

**Backlight** Permanent backlight with all colour schemes

## ENVIRONMENTAL

**Operating temperature range and humidity** -15 °C to +50 °C (5 °F to 122 °F)

**Storage temperature range and humidity** -20 °C to 70 °C (-4 °F to 158 °F)

## ORDERING INFORMATION

Description	Order Code	Description	Order Code
<b>Ordering information</b>		<b>Optional accessories</b>	
TDR2010 UK Dual Channel Comms	1005-447	Fused test lead set	1002-015
TDR2010 EU Dual Channel Comms	1005-448	Replacement battery	1002-552
TDR2010 US Dual Channel Comms	1005-449	Terminal adaptor kit	1003-218
TDR2010 INT Dual Channel Comms	1005-450	Miniature clip test lead set	6231-652
TDR2000/3 UK Time Domain Reflectometer	1003-036	AC power lead - UK	25970-028
TDR2000/3P UK Time Domain Reflectometer	1003-037	AC power lead - EU	6180-334
TDR2000/3 EU Time Domain Reflectometer	1003-339	AC power lead - US	25970-002
TDR2000/3P EU Time Domain Reflectometer	1003-342		
TDR2000/3 US Time Domain Reflectometer	1003-334		
TDR2000/3P US Time Domain Reflectometer	1003-341		
<b>Included accessories</b>			
2 x Miniature Clip Test Lead Set	6231-654		
Dual fused test lead set (2 pairs)	1002-136		
Download kit	1003-353		
Carry case	1003-217		
User guide CD	2003-074		
AC-DC charger	1003-352		

**UK**  
 Archcliffe Road Dover  
 CT17 9EN England  
 T +44 (0) 1304 502101  
 F +44 (0) 1304 207342  
 UKsales@megger.com

**UNITED STATES**  
 4271 Bronze Way  
 Dallas TX 75237-1019 USA  
 T 800 723 2861 (USA only)  
 T +1 214 333 3201  
 F +1 214 331 7399  
 USsales@megger.com

**OTHER TECHNICAL SALES OFFICES**  
 Valley Forge USA, College Station USA,  
 Sydney AUSTRALIA, Danderyd SWEDEN,  
 Ontario CANADA, Trappes FRANCE,  
 Oberursel GERMANY, Aargau SWITZERLAND,  
 Kingdom of BAHRAIN, Mumbai INDIA,  
 Johannesburg SOUTH AFRICA, Chonburi THAILAND

**CERTIFICATION ISO**  
 Registered to ISO 9001:2000 Cert. no. Q 09290  
**TDR2003--TDR2010\_DS\_en\_V07**  
 www.megger.com  
 Megger is a registered trademark

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LAN/Telecom/Cable Testing](#) category:*

*Click to view products by [Megger](#) manufacturer:*

Other Similar products are found below :

[1673606-1](#) [SEFRAM95](#) [TCT-1620](#) [TCT-2210](#) [TCT-680](#) [150050](#) [150058](#) [150059](#) [150060](#) [158050](#) [158051](#) [158053](#) [TCT-2690PRO](#) [TCT-700](#) [TESTER-MS6811](#) [TESTER-MS6812](#) [262](#) [N044-000-R](#) [MCT-468](#) [TM-901N](#) [TM-902](#) [TM-903](#) [LAN-1](#) [24-517](#) [CT20](#) [40180](#) [TG20](#) [GBE FIBRE KIT LX](#) [GBE FIBRE KIT SX](#) [CLM-1000E](#) [CLM-1000](#) [HDMI-100](#) [TEP-100](#) [KE301](#) [KE3100](#) [KE3150](#) [KE401](#) [KE501](#) [KE7000](#) [KE701](#) [KE8000](#) [KE801](#) [KE850](#) [VDV501-851](#) [LANXPLOER PRO](#) [LC-90](#) [NAVITEK IE](#) [NAVITEK NT](#) [NAVITEK NT PLUS](#) [NAVITEK NT PRO](#)