

MEGLADON[®]

MANUFACTURING GROUP, LTD

A TyRex Technology Family Company



4.8mm Ruggedized Indoor / Outdoor Fiber Cables

The Megladon Difference

Megladon's **4.8mm Ruggedized Indoor / Outdoor Fiber Cables** are designed to provide a reliable solution for the challenges associated with multidwelling unit (MDU) deployments and FTTx cabling applications. This 4.8mm cable is a perfect fit for situations which require a rugged drop cable that can be used both indoors and outdoors.

To meet these needs, our product features a durable bend-insensitive fiber which can be stapled directly to rafters or wall studs without risk of damage. Megladon's patented HLC[®] termination process provides increased scratch resistance and maximum durability, while our indoor / outdoor cables are built from the highest-quality materials from the top manufacturers in the fiber cable industry. All assemblies are also factory-terminated and tested to the highest industry standards.

For more information on Megladon's HLC process and products, please visit megladonmfg.com.

KEY BENEFITS

- ✓ Exclusive HLC (Hardened Lens Contact) Manufacturing Process
- ✓ Highly Flexible
- ✓ Indoor / Outdoor Cable Design
- ✓ SCAPC Connectors
- ✓ Staple-Proof Design
- ✓ Bend Insensitive Glass

APPLICATIONS

- ▶ FTTx
- ▶ Outside Plant Fiber
- ▶ MDU Deployments
- ▶ Harsh Environments
- ▶ Broadband Networks



MEGLADON MANUFACTURING GROUP, LTD.
CERTIFIED TO ISO 9001:2015
CERTIFICATE NO. 1092256

4.8mm Ruggedized Indoor / Outdoor Fiber Cables



PERFORMANCE CHARACTERISTICS

ENVIRONMENTAL CHARACTERISTICS

Megladon 4.8mm Ruggedized I/O Fiber Cables			
Wavelength 1310 & 1550	Min	Max	Units
Initial Insertion Loss (HLC)		-0.2	dB
Initial Return Loss (HLC)		-58	dB
Initial Insertion Loss (APCHLC)		-0.2	dB
Initial Return Loss (APCHLC)		-70	dB
Connector Repeatability (IL Change)		0.05	dB
Temperature Cycling (IL Change)		0.05	dB
Temperature Cycling (RL Change)		3	dB
Vibration Loss (IL Change)		0.05	dB
Vibration Loss (RL Change)		3	dB
Cable Retention Loss (IL Change)		0.1	dB
Cable Retention Loss (RL Change)		5	dB

Megladon 4.8mm Ruggedized I/O Fiber Cables			
	Min	Max	Units
Storage Temperature	-40	85	C
Humidity	5	95	% Relative
Bend Radius	10		mm
SM Optical Wavelength	1250	1640	nm
Radius of Curvature (HLC)	7	25	mm
Radius of Curvature (APC)	5	12	mm
Apex Offset	0	50	um
Fiber Height	Fn (ROC)	50	nm
Angle (HLC)	-0.2	0.2	degrees
Angle (APCHLC)	7.5	8.5	degrees

MEGLADON[®]
MANUFACTURING GROUP, LTD

Your Fiber Optic Solutions Partner • Reliable - Rugged - Repeatable

12317 Technology Blvd., Ste. 100 • Austin, Texas • (512) 491-0006 • megladonmfg.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Cable Assemblies](#) category:

Click to view products by [Megladon Manufacturing](#) manufacturer:

Other Similar products are found below :

[7-21002-9](#) [760-1518](#) [FA04390-50-M-72-LC-N](#) [MLB 501 V RED](#) [MLB 501 V YELLOW](#) [1-3636-600-5208](#) [2061529-7](#) [1-6693182-0](#)
[1754898-1](#) [21055-6](#) [FXBSCSCE2LM002](#) [3000005](#) [3-21053-2](#) [MLB 2001 V RED](#) [MLB 2001 V YELLOW](#) [MLB 501 V BLACK](#) [5492011-6](#)
[106284-7000](#) [5492011-5](#) [5492011-8](#) [5492011-9](#) [8-21007-5](#) [2123524-2](#) [2123524-1](#) [106386-4447](#) [DFSM-SCSC-2M](#) [2123909-4](#) [2123909-8](#)
[106273-0629](#) [2125046-1](#) [2821236-3](#) [2821310-2](#) [2821310-3](#) [2821313-4](#) [FX2ERLNLNSNM0.5](#) [CF-980062-074](#) [CF-901200-394](#) [CF-980062-](#)
[073](#) [CF-980062-071](#) [CF-980062-075](#) [CF-980062-072](#) [17-300310-100](#) [2821236-2](#) [2821313-1](#) [G-FC-FC-S-002.0-DX-A-18-Y](#) [G-E2A-E2A-S-](#)
[003.0-SX-A-18-Y](#) [956-322-502214](#) [FA04474](#) [1083665](#) [1111540](#)