

KHE 2444 (606154000) Combination Hammer (220-240 V / 50 Hz); Plastic Carry Case

Order no. 606154000 EAN 4007430203748



Product may differ from Image





- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation

www.metabo.com 1/2



Technical data	
Characteristics	
Max. single blow energy (EPTA)	2.3 J
Maximum impact rate	5400 bpm
Rated input power	800 W
Drill-Ø concrete with hammer drills	24 mm / 1 "
Drill-Ø masonry with core bits	68 mm / 2 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1230 rpm
Revolutions at rated load	880 rpm
Bit retainer	SDS-plus
Collar diameter	43 mm / 1 11/16 "
Weight (without power cable)	2.4 kg / 5.3 lbs
Cable length	4 m / 13 ft
Vibration	
Hammer drilling concrete	13.7 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	15 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	87 dB(A)
Sound power level (LwA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Hammer chuck for tools with SDS-plus shank end

Plastic carry case

Side handle

Drilling depth guide

www.metabo.com 2/2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Screwdrivers, Nut Drivers & Socket Drivers category:

Click to view products by Metabo manufacturer:

Other Similar products are found below:

1406504-2 2-21006-8 27850 CE-16-03400-00-HNDLE-TORQ 30246 323451-000 46722 TL10416 XW4Z-00B 96025 96030 96560 96703 96430 31830 92270 96012 96436 96536 92064 92008 72820 92005 76070 96520 92040 36372 96416 92024 96420 76005 96570 72823 96325 96525 96720 31832 76019 92004 76007 92069 92020 76021 96523 96510 96427 96425 96415 96320 92073