

# New Metcal MX-500 Soldering and Rework System



Metcal's MX-500 Soldering and Rework System has been reimagined, adding features and a new look to a bench top icon. The system utilizes SmartHeat® Technology, wherein each cartridge is equipped with a self-regulating heater which 'senses' its own temperature and closely maintains its pre-set idle temperature for the life of the heater-tip. The tip temperature is determined by the inherent metallurgical properties of the heater; no external adjustment or equipment is required. The MX-500 retains switchable dual port, 40W operation while introducing numerous new features in a new housing.

## FEATURES AND BENEFITS

- **Integrated Power Indication Meter:** a built in net power meter which will display a graphical and numerical representation of the power applied to the cartridge.
- **User Programmable PowerSave Mode:** the time to enter PowerSave Mode is adjustable from 10 to 120 minutes.
- **Ground Fault Interrupt:** AC ground monitor detects power line ground failures and immediately alerts the operator and shuts down the system. Only after the power line ground has been restored, can the MX-500 be restarted and soldering operations can be resumed.
- **Universal Power Supply:** automatically senses the input line voltage and adjusts accordingly, which allows for worldwide operation without adaptors or a change in performance.
- **Compatibility with all MX products:** the MX-500 redesign allows full compatibility with existing and previous MX upgrade kits, tip-cartridges, hand-pieces and accessories.
- **Greater process control with SmartHeat® Technology**
- **Reduced space requirements**

## MX-500 SYSTEMS CONFIGURATION & UPGRADE KITS

### ONE HAND-PIECE SYSTEM

**MX-500S Soldering / Rework System**  
Power supply, MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



### POWER SUPPLY WITHOUT HAND-PIECE

**MX-500P:** MX-500 dual port switchable power supply

### UPGRADE KITS

**MX-UK1:** MX-H1-AV Advanced Soldering and Rework Hand-piece with MX-W1AV TipSaver Workstand



### TWO HAND-PIECE SYSTEMS

**MX-500SPT Rework System**  
Power supply, MX-PTZ precision tweezer hand-piece with MX-W4PT TipSaver workstand and MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



**MX-UK2:** MX-H2-UF Ultra Fine Soldering and Rework Hand-piece with MX-W1AV TipSaver Workstand



**MX-500DS Desoldering System**  
Power supply, MX-DS1 desoldering hand-piece with MX-W5DS TipSaver workstand and MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



**MX-UK4:** MX-PTZ Precision Tweezers Hand-piece with MX-W4PT TipSaver Workstand

**MX-UK5:** MX-DS1 Desoldering Hand-piece with MX-W5DS TipSaver Workstand

**MX-TALON-01:** MX-Talon Tweezer Hand-piece with WST Workstand



HAND SOLDERING SERIES

[www.metcal.com](http://www.metcal.com)

**METCAL**

# New Metcal MX-500 Soldering and Rework System



## HAND-PIECES AND CARTRIDGE SERIES

The MX-500 Series offers users a choice of hand-pieces to meet the customer's application needs. Each hand-piece has its own range of cartridges with many choices available for tip geometry and temperature.

**MX-RM3E**



**MX-H1-AV**



**MX-H2-UF**



**TALON**



**MX-PTZ**



**MX-DS1**



**STTC Soldering & SMT Rework**



**UFTC Ultra-Fine**



**TATC TALON**



**PTTC Tweezers**



**STDC Desolder**



These six hand-pieces are compatible with the Metcal MX-500 and MX-5200 Soldering and Rework Systems.

## ACCESSORIES

AC-Y10	Yellow sponge, pack of 10	WS1	Sleeper Soldering Workstand
AC-BP	Brass pad, pack of 10	MX-W1AV	TipSaver Soldering Workstand
AC-BRUSH	Soft Brass brush	MX-W4PT	TipSaver Precision Tweezer Workstand
MX-CP1	Cartridge removal pad	MX-W5DS	TipSaver Desoldering Workstand
AC-TC	Desolder Tip Cleaner	WST	Talon Workstand

## TECHNICAL SPECIFICATIONS

Ambient Operating Temperature	10 to 40°C
Maximum Enclosure Temperature	55°C
Input Line Voltage	100 – 240 VAC, grounded circuit
Input Line Frequency	50/60 Hz
Rated Power Consumption	70 Watts
<b>Output Power</b>	<b>40 Watts max. *</b>
<b>Output Frequency</b>	<b>13.56 MHz *</b>
Power Supply Dimensions w x d x h	12.1cm (4.8") x 12.1cm (4.8") x 22.2cm (8.8")
Certification / Marking	cNRTLus, CE
Tip-to- Ground Potential	<2mV
Tip-to-Ground Resistance	<2 ohms
Idle Temperature Stability	± 1.1°C in still air
Hand-piece Cable Length	L=183cm (72"), burn proof, ESD safe
Hand-piece Connector	F connector
Weight of the power supply	2.65 Kg (5.85 lbs)

\* RF SmartHeat Technology provides greater power.  
More details at [www.metcal.com/smartheat](http://www.metcal.com/smartheat)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Soldering Irons](#) category:*

*Click to view products by [Metcal](#) manufacturer:*

Other Similar products are found below :

[918100-TE](#) [PTTC-802](#) [SFV-DRK30AR](#) [SMTC-0167](#) [SMTC-588](#) [AC-CK1](#) [AC-CK2](#) [SSC-601A](#) [SSC-625A](#) [SSC-626A](#) [SSC-638A](#) [SSC-726A](#) [FG-BVX](#) [STTC-042](#) [STTC-065](#) [STTC-114](#) [STTC-838P](#) [STV-CH24A](#) [UFTC-6CN04](#) [SFP-DRH05](#) [SMTC-005](#) [SMTC-061](#) [SMTC-101](#) [SMTC-1162](#) [SMTC-160-PK](#) [SMTC-1BL250](#) [SMTC-862](#) [SSC-645A](#) [SSC-671A](#) [SSC-713A](#) [SSC-745A](#) [SSC-746A](#) [SSC-772A](#) [STDC-804](#) [STTC-105](#) [STTC-120](#) [STTC-545](#) [1-91362-0](#) [T0054487399](#) [T0054472199](#) [T0054465699](#) [STTC-820](#) [SMTC-116](#) [SMTC-004](#) [MX-H1GKG](#) [SCV-CH30AR](#) [T0054440699](#) [STTC-845P](#) [RPS-1](#) [SMTC-006](#)