

# New Metcal MX-500 Soldering and Rework System



Metcal's MX-500 Soldering and Rework System has been reimagined, adding features and a new look to a bench top icon. The system utilizes SmartHeat® Technology, wherein each cartridge is equipped with a self-regulating heater which 'senses' its own temperature and closely maintains its pre-set idle temperature for the life of the heater-tip. The tip temperature is determined by the inherent metallurgical properties of the heater; no external adjustment or equipment is required. The MX-500 retains switchable dual port, 40W operation while introducing numerous new features in a new housing.

## FEATURES AND BENEFITS

- **Integrated Power Indication Meter:** a built in net power meter which will display a graphical and numerical representation of the power applied to the cartridge.
- **User Programmable PowerSave Mode:** the time to enter PowerSave Mode is adjustable from 10 to 120 minutes.
- **Ground Fault Interrupt:** AC ground monitor detects power line ground failures and immediately alerts the operator and shuts down the system. Only after the power line ground has been restored, can the MX-500 be restarted and soldering operations can be resumed.
- **Universal Power Supply:** automatically senses the input line voltage and adjusts accordingly, which allows for worldwide operation without adaptors or a change in performance.
- **Compatibility with all MX products:** the MX-500 redesign allows full compatibility with existing and previous MX upgrade kits, tip-cartridges, hand-pieces and accessories.
- **Greater process control with SmartHeat® Technology**
- **Reduced space requirements**

## MX-500 SYSTEMS CONFIGURATION & UPGRADE KITS

### ONE HAND-PIECE SYSTEM

**MX-500S Soldering / Rework System**  
Power supply, MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



### POWER SUPPLY WITHOUT HAND-PIECE

**MX-500P:** MX-500 dual port switchable power supply

### UPGRADE KITS

**MX-UK1:** MX-H1-AV Advanced Soldering and Rework Hand-piece with MX-W1AV TipSaver Workstand



### TWO HAND-PIECE SYSTEMS

**MX-500SPT Rework System**  
Power supply, MX-PTZ precision tweezer hand-piece with MX-W4PT TipSaver workstand and MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



**MX-UK2:** MX-H2-UF Ultra Fine Soldering and Rework Hand-piece with MX-W1AV TipSaver Workstand



**MX-500DS Desoldering System**  
Power supply, MX-DS1 desoldering hand-piece with MX-W5DS TipSaver workstand and MX-RM3E soldering and rework hand-piece and WS1 sleeper workstand



**MX-UK4:** MX-PTZ Precision Tweezers Hand-piece with MX-W4PT TipSaver Workstand

**MX-UK5:** MX-DS1 Desoldering Hand-piece with MX-W5DS TipSaver Workstand

**MX-TALON-01:** MX-Talon Tweezer Hand-piece with WST Workstand



HAND SOLDERING SERIES

[www.metcal.com](http://www.metcal.com)

**METCAL**

# New Metcal MX-500 Soldering and Rework System



## HAND-PIECES AND CARTRIDGE SERIES

The MX-500 Series offers users a choice of hand-pieces to meet the customer's application needs. Each hand-piece has its own range of cartridges with many choices available for tip geometry and temperature.

**MX-RM3E**



**MX-H1-AV**



**MX-H2-UF**



**TALON**



**MX-PTZ**



**MX-DS1**



**STTC Soldering & SMT Rework**



**UFTC Ultra-Fine**



**TATC TALON**



**PTTC Tweezers**



**STDC Desolder**



These six hand-pieces are compatible with the Metcal MX-500 and MX-5200 Soldering and Rework Systems.

## ACCESSORIES

AC-Y10	Yellow sponge, pack of 10	WS1	Sleeper Soldering Workstand
AC-BP	Brass pad, pack of 10	MX-W1AV	TipSaver Soldering Workstand
AC-BRUSH	Soft Brass brush	MX-W4PT	TipSaver Precision Tweezer Workstand
MX-CP1	Cartridge removal pad	MX-W5DS	TipSaver Desoldering Workstand
AC-TC	Desolder Tip Cleaner	WST	Talon Workstand

## TECHNICAL SPECIFICATIONS

Ambient Operating Temperature	10 to 40°C
Maximum Enclosure Temperature	55°C
Input Line Voltage	100 – 240 VAC, grounded circuit
Input Line Frequency	50/60 Hz
Rated Power Consumption	70 Watts
<b>Output Power</b>	<b>40 Watts max. *</b>
<b>Output Frequency</b>	<b>13.56 MHz *</b>
Power Supply Dimensions w x d x h	12.1cm (4.8") x 12.1cm (4.8") x 22.2cm (8.8")
Certification / Marking	cNRTLus, CE
Tip-to- Ground Potential	<2mV
Tip-to-Ground Resistance	<2 ohms
Idle Temperature Stability	± 1.1°C in still air
Hand-piece Cable Length	L=183cm (72"), burn proof, ESD safe
Hand-piece Connector	F connector
Weight of the power supply	2.65 Kg (5.85 lbs)

\* RF SmartHeat Technology provides greater power.  
More details at [www.metcal.com/smartheat](http://www.metcal.com/smartheat)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Soldering & Desoldering Stations](#) category:*

*Click to view products by [Metcal](#) manufacturer:*

Other Similar products are found below :

[GS1116](#) [T0053650699](#) [BH-010](#) [T0058768747](#) [CA0202](#) [CA0201](#) [WXD2N](#) [T0058757898](#) [T0058768743N](#) [T0051512199N](#) [145-2000-ESDN](#)  
[T0058758721N](#) [WTL1000-1](#) [T0058768725N](#) [TS2300D](#) [WELPB102](#) [0019208](#) [0780550](#) [CVC-7CN0004P](#) [CVC-9CH0025S](#) [CVC-8CH0010S](#)  
[CV-H5-DSHP](#) [SL916-NI](#) [0016344](#) [00B.SA.0](#) [0352830](#) [0460MDJ](#) [0551903](#) [0965970](#) [0DIG20A45](#) [0IC1100A](#) [0ICV2000XV](#) [0.SA.0](#) [0T56](#)  
[CL-SFE/1 FILTERS](#) [PX0410/03P/5055](#) [RA150](#) [35464](#) [10G.SA.0](#) [10LL4](#) [3C.SA](#) [3.TA](#) [AT850D/P](#) [TMT-HA300](#) [TMT-PH200](#) [TMT-PH300](#)  
[5-048](#) [5-050](#) [5-051](#) [5-052](#)