

## Description

The 433C *d-Limonene* is an industrial grade solvent. It is a biodegradable product with a pleasant odor.

## Applications & Usages

The 433C will dissolve HIPS (High Impact Polystyrene) used in 3D printing applications for creating support material.

It can also be used for many other applications, such as removing adhesives and tar, cleaning floors, and degreasing. It also works well as a hand cleaner, a release agent, and as graffiti remover.

It can replace petroleum-derived products in many different applications.

## Features and Benefits

- **Biodegradable solvent and cleaning agent**
- **100% bio-based**—free of any petroleum product
- **RoHS Compliant**

**ATTENTION!** FOR INDUSTRIAL OR LABORATORY USE ONLY. NOT FOR RETAIL SALE IN CALIFORNIA, UTAH, AND NEW HAMPSHIRE.

## Usage Parameters

<i>Properties</i>	<i>Value</i>
Shelf Life	5 y

## Temperature Ranges

<i>Properties</i>	<i>Value</i>
Storage Temperature Limits <sup>a)</sup>	-20 to 40 °C [-4 to 104 °F]

a) Store in cool, dry, and well ventilated area.

## d-Limonene Properties

<i>Physical Properties</i>	<i>Value</i>
Appearance	Colorless
Specific Gravity @25 °C [77 °F]	0.85 g/mL
Water Solubility	Slightly soluble
Refractive Index	1.468–1.478
Flash Point, Closed Cup	31 °C [88 °F]

## Health and Safety

Please see the 433C-Liquid **Safety Data Sheet** (SDS) for more details on transportation, storage, handling and other security guidelines.

**Environmental Impact:** The volatile organic content is 100% by EPA and WHMIS standards. It is toxic to aquatic life in high concentration. Please dispose of in accordance to local/regional/national/international regulations.




This product meets the European Directive 2011/65/EU Annex II (ROHS); recasting 2002/95/EC.

**Health and Safety:** May cause allergic reaction and skin irritation in some individuals. Wash hands thoroughly after use. Aspiration of d-limonene into the lung may be fatal.

### HMIS® RATING

<b>HEALTH:</b>	<b>1</b>
<b>FLAMMABILITY:</b>	<b>2</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

### NFPA® 704 CODES



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

## Application Instructions

### To dissolve 3D support structures

1. Place the d-limonene solution in a sealable jar.
2. Place the print in the jar.
3. (Optional) Shake or agitate the jar periodically.

## Packaging and Supporting Products

<i>Cat. No.</i>	<i>Packaging</i>	<i>Net Volume</i>	<i>Net Weight</i>	<i>Packaging Weight</i>
<b>433C-1L</b>	Can	945 mL    1.99 pt	799 g    1.76 lb	TBD
<b>433C-4L</b>	Can	3.78 L    1 gal	3.19 kg    7.05 lb	"

TBD=To be determined



ISO 9001 Registered Quality System.  
Burlington, Ontario, Canada QMI File # 004008

# d-Limonene—Industrial Strength 433C Technical Data Sheet

433C-Liquid

## Technical Support

Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: +(1) 800-340-0772 (Canada, Mexico & USA)  
+(1) 905-331-1396 (International)

Fax: +(1) 905-331-2862 or +(1) 800-340-0773

Mailing address: **Manufacturing & Support**  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

**Head Office**  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

## Warranty

*M.G. Chemicals Ltd.* warrants this product for 12 months from the date of purchase by the end user. *M.G. Chemicals Ltd.* makes no claims as to shelf life of this product for the warranty. The liability of *M.G. Chemicals Ltd.* whether based on its warranty, contracts, or otherwise shall in no case include incidental or consequential damage.

## Disclaimer

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. *M.G. Chemicals Ltd.* does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Soldering Flux](#) category:*

*Click to view products by [MG Chemicals](#) manufacturer:*

Other Similar products are found below :

[24-6337-9727](#) [051-0001](#) [051-0002](#) [051-0003](#) [051-0004](#) [051-0007](#) [051-0008](#) [051-0009](#) [051-0010](#) [053-1002](#) [053-1003](#) [CW8700](#) [CW8300](#)  
[SMD4300TF10](#) [SMD291/30CC](#) [CQ2LF](#) [CQ4LF](#) [8342-50G](#) [270WR](#) [ART.AGT-094](#) [CW8100](#) [CW8400](#) [CW8500](#) [CQ4LF-0.5](#) [CQ4LF-1.0](#)  
[SMD291](#) [SMD291150G](#) [SMD29175G](#) [SMD291AX](#) [SMD291AX10](#) [SMD291AX250T3](#) [SMD291AX250T5](#) [SMD291ST2CC6](#)  
[SMD291ST8CC](#) [SMD4300TF](#) [CW8100](#) [CW8200](#) [63-0000-0951](#) [63-0000-0977](#) [63-0000-1544](#) [83-1000-0186](#) [83-1097-2331](#) [760089](#) [8341-](#)  
[10ML](#) [8341-10ML](#) [835-100ML](#) [837-P](#) [SF-01](#) [SF-02](#) [2506-N](#)