



**BRIGHTTEK**  
**BRIGHTTEK (EUROPE) LIMITED**

*Brighten up The World With LED!*



ISO/TS 16949:2009



BS EN ISO 14001:2004



QC 080000 IECQ HSPM

## PRODUCT DATASHEET



- ▶ PLCC4 SMD with IC
- ▶ 3535 IC 1.9t
- ▶ Red/Green/Blue

NOM59S09IC



Release Date: 26 April 2021 Version: A1.0



### 3535 IC-Integrated

**RoHS**  
Compliant



#### FEATURES:

- **Package:** PLCC4 Top View Package with Integrated IC
- **Forward Current:** 20/20/20mA\*
- **Forward Voltage (typ.):** +3.3~+5.5V
- **Luminous Intensity (typ.):** 820/1350/290mcd
- **Colour:** Red/Green/Blue
- **Wavelength:** 622/520/470nm
- **Viewing angle:** 120°
- **Materials:**
  - Resin: Silicone (Water Clear)
  - L/F Finish: Ag Plated
- **Operating Temperature:** -40~+85°C
- **Storage Temperature:** -40~+100°C
- **Pixel:** Each R/G/B chip is 8bit, total of 16M colours can be displayed
- **Soldering methods:** IR Reflow soldering
- **Preconditioning:** acc. to JEDEC Level 4
- **Packing:** 12mm tape with Max.500pcs/reel, ø180mm (7")

\* in order of Red/Green/Blue

#### APPLICATIONS:

- Telecommunication
- Indicator
- Home Appliance
- Decoration Lighting
- Full Colour LED Strip
- Gaming Device
- Guardrail Tube

**CHARACTERISTICS:**

## Absolute Maximum Characteristics (Ta=25°C)


Parameter	Symbol	Ratings	Unit
LED Output Current	I <sub>OUT</sub>	25	mA
Supply Voltage	V <sub>DD</sub>	0 ~ +6.0	V
Power Dissipation	P <sub>D</sub>	400	mW
Operating Temperature	T <sub>OPR</sub>	-40~+85	°C
Storage Temperature	T <sub>STG</sub>	-40~+100	°C

 Electrical & Optical Characteristics (Ta=25°C, V<sub>DD</sub>=5V)

Parameter	Symbol	Values			Unit	Test Condition	
		Min.	Typ.	Max.			
Forward Voltage	V <sub>F</sub>	3.3	5.0	5.5	V	---	
Each R/G/B Current	I <sub>OL</sub>	---	20	---	mA	V <sub>DD</sub> =5V	
Input High Voltage	V <sub>IH</sub>	2.7	---	V <sub>DD</sub>	V	DI	
Input Low Voltage	V <sub>IL</sub>	0	---	1.0	V	DI	
Output High Voltage	V <sub>OH</sub>	4.5	---	---	V	I <sub>OH</sub> =4mA	
Output Low Voltage	V <sub>OL</sub>	---	---	0.4 V <sub>DD</sub>	V	I <sub>OL</sub> =4mA	
Operation Current	I <sub>DD</sub>	---	---	2	mA	B, G, R no load	
Pull Down Resistance	R <sub>PD</sub>	---	500K	---	Ω	D <sub>IN</sub> , D <sub>OUT</sub> (V <sub>DD</sub> =5V)	
Luminous Intensity	R	I <sub>V</sub>	---	820	---	mcd	I <sub>F</sub> =20mA
	G		---	1350	---		
	B		---	290	---		
Dominant Wavelength	R	λ <sub>D</sub>	---	622	---	nm	I <sub>F</sub> =20mA
	G		---	520	---		
	B		---	470	---		
Viewing Angle	2θ <sub>1/2</sub>	---	120	---	deg	I <sub>F</sub> =20mA	


## OUTLINE DIMENSION:

### Package Dimension:




1. All dimensions are in millimetre (mm).
2. Tolerance  $\pm 0.2\text{mm}$ , unless otherwise noted.

### Recommended Soldering Pad Dimension:




1. Dimensions are in millimetre (mm).
2. Tolerance  $\pm 0.1\text{mm}$  with angle tolerance  $\pm 0.5^\circ$ .

**PIN CONFIGURATION:**


No.	Symbol	Function Description
1	VDD	DC Power Input
2	DOUT	Control Data Signal Output
3	VSS	Ground
4	DIN	Control Data Signal Input


## Function Description:

### 1. Timing Wave Form:




Item	Description	min	Typical	Allowance	unit
T0H	0 code, High-level time		0.3	±0.15	us
T0L	0 code, Low-level time		0.9	±0.15	us
T1H	1 code, High-level time		0.9	±0.15	us
T1L	1 code, Low-level time		0.3	±0.15	us
Trst	Reset code, Low-level time	250			us

### 2. Data Communication:




### 3. Single Data in 24bit for RGB:



## RECOMMENDED SOLDERING PROFILE:

---

Lead-free Solder IR Reflow:




Note:

1. We recommend the reflow temperature 240°C ( $\pm 5^\circ\text{C}$ ). The maximum soldering temperature should be limited to 260°C.
2. Maxima reflow soldering: 2 times.
3. Before, during, and after soldering, should not apply stress on the components and PCB board.

**PACKING SPECIFICATION:**

Reel Dimension:



## PRECAUTIONS OF USE:

---

### Storage:

It is recommended to store the products in the following conditions:

- Humidity: 60% R.H. Max.
- Temperature: 5°C~30°C (41°F ~86°F).

Shelf life in sealed bag: 12 months at 5°C~30°C and <60% R.H.

Once the package is opened, the products should be used within 72 hours. Otherwise, they should be kept in a damp-proof box with desiccating agent stored at R.H.<10% and apply baking before use.

### Over-Current Proof:

Must apply resistors for protection otherwise slight voltage shift will cause big current change and burn-out will happen.


### Baking:

It is recommended to bake the LED before soldering if the pack has been unsealed for longer than 24hrs. The suggested baking conditions are as followings:

- 60±5°C x 24hrs and <5%RH, taped / reel package.

It's normal to see slight color fading of carrier (light yellow) after baking in process.

### Recommended Route:



### Cleaning:

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED carrier / package. Avoid putting any stress force directly on to the LED lens.

### ESD (Electrostatic Discharge):

Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrostatic glove is recommended when handling the LED all time. All devices, equipment, machinery, work tables, and storage racks must be properly grounded.



**REVISION RECORD:**

---

Version	Date	Summary of Revision
A1.0	26/04/2021	Datasheet set-up.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard LEDs - SMD category](#):*

*Click to view products by [MGT Brightek manufacturer](#):*

Other Similar products are found below :

[LTST-C190KYKT](#) [LTST-C19GD2WT](#) [LTW-170ZDC](#) [LTW-M140SZS40](#) [LTW-M140ZVS](#) [598-8110-100F](#) [598-8610-202F](#) [91-21SUBCS400-A6TR7](#) [AAAF5060QBFSEEZGS](#) [APT1608QGW](#) [99-213/R6C-AR2T1B/2C](#) [SML-LX0606SISUGC/A](#) [SML-LXR851SIUPGUBC](#) [LT1ED53A](#) [APFA3010SURKCGKQBDC](#) [APHK1608VGCA](#) [APT2012QGW](#) [LTST-008BGEW](#) [LTW-010DCG](#) [LTW-020ZDCG](#) [LTW-21TS5](#) [LTW-220DS5](#) [598-8330-117F](#) [65-21SYGC/S530-E3/TR8](#) [CMDA20AYAA7D1S](#) [95-21SURCS530-A3TR10](#) [598-8040-100F](#) [598-8070-100F](#) [598-8140-100F](#) [598-8610-200F](#) [SML-LXR851SGSIC-TR](#) [SML-512PWT86A](#) [SMF-2432GYC-TR](#) [EASV3015RGYA0](#) [95-21UYC-S530-A5-TR7](#) [LTST-C190KFKT-5A](#) [LTST-C194TBKT-5A](#) [CLX6E-FKC-CH1M1D1BB7C3D3](#) [SML-LXL0805USBC-TR](#) [SML-LX2835SYSUGCTR](#) [LTW-M670ZVS-M5](#) [APA2106ZGC/G](#) [CLMXB-FKA-CbcfghjnpACBB79463](#) [VFA1101W-5AY3B2-TR](#) [LCB P473-P2R2-3J7L-1-Z](#) [91-21VGC/S556/S68/TR10/S370](#) [LW A67C-S2U1-FK0KM0](#) [LW A673-P1S1-FK0PM0](#) [BL-HE1G033B-TRB](#) [5988B90107F](#)