

CM031005 SPECIFICATIONS

Holder: HC-45/U

Frequency: See Table

Mode: Fundamental

Load Capacitance: TBD

Frequency stability: ± 150 ppm, -15° to 175°C with respect to nominal frequency.


Series Resistance: 25 ohms Max.

Reference HC-45/U Cold Weld Small Footprint Outline drawing for dimensions.

A sample of crystals from each production run shall be subjected to vibration in accordance with MIL-STD-202, Method 204, Test Condition D except the frequency range shall be 10 Hz to 500 Hz. The change in operating frequency of the crystals shall not exceed 5 ppm, and the change in series resistance shall not exceed 10%.

Part Number	Frequency	Motional Capacitance
CM031005-12	12.000 MHz	12.0 pF
CM031005-16	16.000 MHz	16.0 pF
CM031005-18	18.432 MHz	18.0 pF
CM031005-25	25.000 MHz	20.0 pF

Crystals are manufactured for high temperature operation up to 175°C : holder, leads, and electrodes are Gold plated. Polyimide cement is used internally.

APPROVALS	NAME	INITIALS	DATE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES: FRACTIONS 2 - PLACE 3 - PLACE ANGLES DECIMALS DECIMALS $\pm 1/64"$ $\pm 0.020"$ $\pm 0.005"$ $\pm 1/2^{\circ}$		
DRAWN						
ENGINEERING MANAGER						
PRODUCTION MANAGER						
QUALITY ASSURANCE						
		DRAWING NUMBER CM031005		REV.		
Fundamental Mode High Temperature AT-Cut Crystal						
VI CINOX 4914 Gray Road - Cincinnati, OH 45232		FSCM NUMBER 58997	SCALE	DATE ISSUED 3/23/2005	SIZE A	SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Crystals](#) category:

Click to view products by [Microchip](#) manufacturer:

Other Similar products are found below :

[MC405 32.0000K-R3:PURE SN](#) [7B-27.000MBBK-T](#) [MP1-8.0 99-BU](#) [9B-15.360MBBK-B](#) [PTX-A2JM-10.000M](#) [9C-7.680MBBK-T](#) [H10S-12.000-18-EXT-TR](#) [R38-32.768-12.5-5PPM-NPB](#) [BTD1062E05A-513](#) [21U15A-21.4MHZ](#) [RTX-781DF1-S-20.950](#) [LFXTAL066198Cutt](#) [9C-14.31818MBBK-T](#) [A-11.000MHZ-27](#) [SPT2A-.032768B](#) [SPT2A.032768G](#) [SSPT7F-9PF20-R](#) [FX325BS-38.88EEM1201](#) [MP-1-6.000MHZ](#) [LFXTAL065253Cutt](#) [LFXTAL066431Cutt](#) [XT9S20ANA14M7456](#) [XT9SNLANA16M](#) [646G-24-2](#) [7B-30.000MBBK-T](#) [6504-202-1501](#) [6526-202-1501](#) [BTJ120E02C](#) [SG636PCE-20.000MC](#) [3404](#) [ABL-4.000MHZ-DI](#) [CX3225SB48000Z0DZNC1](#) [CM315D32768EZFT](#) [C1E-24.000-7-2020-R](#) [C1E-19.200-12-1530-X-R](#) [C1E-16.000-12-1530-X-R](#) [FL5000014](#) [EUCA18-3.1872M](#) [425F35E027M0000](#) [FP0800018](#) [17196](#) [MS3V-T1R-32.768kHz-7pF-20PPM-TA-QC-Au](#) [VXM7-1C1-16M000](#) [MS1V-T1K-32.768kHz-10pF-20PPM-TA-QC-Au](#) [MS1V-T1K-32.768kHz-12.5pF-20PPM-TA-QC-Au](#) [MS3V-T1R-32.768kHz-9pF-20PPM-TA-QC-Au](#) [CX2016DB48000C0FPLC1](#) [17000](#) [17301](#)