

8-pin DIP Device Adapters	
DVA12XP080	PIC12C5XX pinout 2.5V – 5.5V operation
DVA12XP081	PIC12C67X pinout 2.5V – 5.5V operation Processor module connections differ from DVA12XP080
14-pin DIP Device Adapters	
DVA16XP140	PIC16C505 pinout 2.5V – 5.5V operation
DVA16XP141	PIC16F676 pinout 2.5V – 5.5V operation
18-pin DIP Device Adapters	
DVA16XP180	PIC16C5X pinout 2.5V – 5.5V operation
DVA16XP182	PIC16C716 pinout 2.5V – 5.5V operation Timer1 oscillator on RB1/RB2 (Controlled by switches) Processor module connections differ from DVA16XP180
DVA16XP187	PIC16F716 pinout 2.5V – 5.5V operation Timer1 oscillator on RB1/RB2 (Controlled by switches) Processor module connections differ from DVA16XP182
DVA16XP183	PIC16F628 pinout 2.5V – 5.5V operation Timer1 oscillator on RB6/RB7
DVA16XP186	PIC16F648A pinout 2.5V – 5.5V operation Timer1 oscillator on RB6/RB7 Processor module connections differ from DVA16XP183
DVA16XP184	PIC16C717 pinout 2.5V – 5.5V operation
DVA18XP180	Supersedes DVA16XP184 2.5V – 5.5V operation Allows Timer1 oscillator to function properly on PIC18F devices
DVA16XP185	PIC16C433 pinout 2.5V – 5.5V operation
DVA1001	Supersedes DVA16XP187 PIC16F716 pinout Added support for 2.0V – 5.5V Operation Timer1 oscillator on RB1/RB2 (Software controlled by T1OSCEN bit in T1CON)
DVA1006	Supersedes DVA16XP186 PIC16F648A pinout Added support for 2.0V – 5.5V Operation Timer1 oscillator on RB6/RB7
20-pin DIP Device Adapters	
DVA16XP200	PIC16C770 pinout 2.5V – 5.5V operation Timer1 oscillator on RB6/RB7
DVA16XP201	PIC16C432 pinout 2.5V – 5.5V operation
DVA16XP202	PIC16C782 pinout 2.5V – 5.5V operation Timer1 oscillator on OSC1/OSC2
28-pin DIP Device Adapters	
DVA14XP280	PIC14000 pinout 2.5V – 5.5V operation
DVA16XP280	PIC16C5X pinout 2.5V – 5.5V operation
DVA16XP281	PIC16C6X/7X pinout

	2.5V – 5.5V operation
DVA16XP282	Supersedes DVA16XP281
	2.5V – 5.5V operation
	Added support for RA6 digital I/O
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA18XP280	Added support for Timer1 oscillator
	Supersedes DVA16XP282
	2.5V – 5.5V operation
	Added support for RA7 digital I/O
40-pin DIP Device Adapters	Added support for OSC2 (FOSC/4) clock out frequency in Primary, RC and Secondary oscillator modes
DVA16XP400	PIC16C6X/7X pinout
	2.5V – 5.5V operation
DVA16XP401	Supersedes DVA16XP400
	2.5V – 5.5V operation
	Added support for RA6 digital I/O
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA17XP400	Added support for Timer1 Oscillator
	PIC17C4X pinout
	2.5V – 5.5V operation
DVA17XP401	Supersedes DVA17XP400
	2.5V – 5.5V operation
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA18XP400	Supersedes DVA16XP401
	2.5V – 5.5V operation
	Added support for RA7 digital I/O
	Added support for OSC2 (FOSC/4) clock out frequency in Primary, RC and Secondary oscillator modes
44-pin TQFP Device Adapters	
DVA16PQ440	PIC16C6X/7X pinout
	2.5V – 5.5V operation
DVA16PQ441	Supersedes DVA16PQ440
	2.5V – 5.5V operation
	Added support for RA6 digital I/O
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA17PQ440	Added support for Timer1 Oscillator
	PIC17C4X pinout
	2.5V – 5.5V operation
DVA17PQ441	Supersedes DVA17PQ440
	2.5V – 5.5V operation
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA18PQ440	Supersedes DVA16PQ441
	2.5V – 5.5V operation
	Added support for RA7 digital I/O
	Added support for OSC2 (FOSC/4) clock out frequency in Primary, RC and Secondary oscillator modes
44-pin PLCC Device Adapters	
DVA16XL440	PIC16C6X/7X pinout
	2.5V – 5.5V operation
DVA16XL441	Supersedes DVA16XL440
	2.5V – 5.5V operation
	Added support for RA6 digital I/O
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA17XL440	Added support for Timer1 oscillator
	PIC17C4X pinout
	2.5V – 5.5V operation
DVA17XL441	Supersedes DVA17XL440
	2.5V – 5.5V operation
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode

64-pin DIP Device Adapter	
DVA16XP640	PIC16C923/924 pinout
	2.5V – 5.5V operation
64-pin TQFP Device Adapter	
DVA16PQ640	PIC16C92X pinout
	2.5V – 5.5V operation
DVA17PQ640	PIC17C75X pinout
	2.5V – 5.5V operation
DVA17PQ641	Supersedes DVA17PQ640
	2.5V – 5.5V operation
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA18PQ640	PIC18C658 pinout
	2.5V – 5.5V operation
68-pin PLCC Device Adapter	
DVA16XL680	PIC16C92X pinout
	2.5V – 5.5V operation
DVA17XL680	PIC17C75X pinout
	2.5V – 5.5V operation
DVA17XL681	Supersedes DVA17XL680
	2.5V – 5.5V operation
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA18XL680	PIC18C658 pinout
	2.5V – 5.5V operation
80-pin TQFP Device Adapter	
DVA17PQ800	PIC17C76X pinout
	2.5V – 5.5V operation
DVA17PQ801	Supersedes DVA17PQ800
	2.5V – 5.5V operation
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA18PQ800	PIC18C858 pinout
	2.5V – 5.5V operation
84-pin PLCC Device Adapter	
DVA17XL840	PIC17C76X pinout
	2.5V – 5.5V operation
DVA17XL841	Supersedes DVA17XL840
	2.5V – 5.5V operation
	Added support for OSC2 (FOSC/4) clock out in EC oscillator mode
DVA18XL840	PIC18C858 pinout
	2.5V – 5.5V operation
8/14-pin DIP Device Adapter	
DVA1002	Supersedes DVA16XP141
	Added support for 2.0V – 5.5V Operation
	Added support for Ultra Low Power Wake-up
	Added support for OSC2 (FOSC/4) clock out in INTOSC-CLK oscillator mode
8/14/20-pin DIP Device Adapter	
DVA1004	Supersedes DVA1002
	2.0V – 5.5V Operation
	Added support for 20-Pin Devices
64-pin TQFP/80-pin TQFP Device Adapter	
DVA18PQ802	PIC18F6680/8680 pinout
	2.5V – 5.5V operation
DVA1003	Supersedes DVA18PQ802
	Added support for RA7 digital I/O
	Added support for 2.0V – 5.5V Operation

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Sockets & Adapters](#) category:

Click to view products by [Microchip](#) manufacturer:

Other Similar products are found below :

[6508-0-00-01-00-00-33-0](#) [AC164341](#) [AC164348](#) [1262](#) [C8051F350-TB](#) [KITPF0100SKTEVBE](#) [LFVDBJR](#) [AC164334](#) [AC164383](#) [SOCKET-ADM106XTQZ](#) [SPC564A80CAL176](#) [ST5M1267-001](#) [CY3675-LCC4A](#) [TDGL015](#) [ATF15XXDK3-SAA100](#) [LFBGADATC](#) [SM64TQ-ACTEL-1](#) [AC164358](#) [ATSTK600-RC99](#) [76002056](#) [DS91230+](#) [OM13019,598](#) [09185058](#) [AC164369](#) [AC164409](#) [AC164402](#) [SMPA-ISP-ACTEL-3-KIT](#) [ICESABCM81-01](#) [LFVDBGF](#) [AC164408](#) [KIT 70601-3](#) [S5U13U00P00C100](#) [AC164352](#) [PN-Q208/5256V](#) [PN-T100/LC4256](#) [AC164370](#) [AC164355](#) [AC164367](#) [CY3675-TSSOP20B](#) [SPC563M64AVB144](#) [ATF15XXDK3-SAA44](#) [AC164410](#) [SPC563M64AVB176](#) [SM132CQ-ACTEL](#) [AC164398](#) [CX5103](#) [IPC0165-S](#) [R0E000010ACB20](#) [AC164368](#) [ADALM-UARTJTAG](#)